NOTICE TO WATER WELL CONTRACTOR
The original and first conv

MAY 17 1967

The original and first copy of this report are to be filled with the STATE ENGINEER, SALEM, OREGON 97310 STATE ENGINEER, SALEM, OREGON 97310 Within 30 days from the date of well completion.

STATE OF OREGON
(Please type or print) G-3937

State Permit No.

1) OWNER:	(11) WELL TESTS: Drawdown is amount volume to lowered below static levels and the static levels are the static levels and the static levels are the static	vater leve zel	l is
Tame FRANK W. GROVES	Was a pump test made? Yes \[\] No If yes, by whom	2 /1 1KI	Elfrelm
Address 147 MARIA ST LEBANON ORR	Yield: 500 gal./min. with 2 ft. drawdow		3 hrs.
	" "	,	<u>"</u>
2) LOCATION OF WELL:	" "		
	Bailer test gal./min. with ft. drawdo	wn after	hrs.
County //// Driller's well number	Artesian flow g.p.m. Date		
14 14 Section 29 T. 10 S R. 2 W.M.	Temperature of water Was a chemical analysis r		
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below ca	sing	0
	Depth drilled 37 ft. Depth of completed wel	a 27	7 ft.
	Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of t		cture, and
	show thickness of aquifers and the kind and nature of t stratum penetrated, with at least one entry for each cl	he materi ıange of ;	al in each formation.
		FROM	TO
(3) TYPE OF WORK (check):	MATERIAL	FROM	
	BROWN SANDY CLAY	0	9
Well	Bhore - Chry	9	7
ir coandonment, describe material and procedure in Item 12.	UNGONSOLIDATED CUORSIE	7	
(4) PROPOSED USE (check): (5) TYPE OF WELL:	GRAVEL & SAND	14	5 /
Domestic Industrial Municipal Rotary Driven	BROWN - GLAY	91	27
rrigation Test Well C Other C Cable G Jetted L	UNCONSULIDATED SAND +	21	<u> </u>
Dug Bored	GRAVEL		
(6) CASING INSTALLED: Threaded Welded		1	
// Diam. from // ft. to			سقوب سند دقع
ft. to ft. Gage ft.		+	
(7) PERFORATIONS: Perforated? Yes No			
Type of perforator used Torch			,
Size of perforations in. by in.			1
perforations from ft. to ft. gt. gerforations from ft. to 7. gt. gt. to 7. gt.			
perforations from ft. to ft.			
perforations from ft. to ft.			:-
perforations from ft. to ft.			
(8) SCREENS: Well screen installed? ☐ Yes ♥No			
Manufacturer's Name			
e			
Diam Slot size Set from ft. to ft.	Work started 3/3/69 19 Completed 3	12/6	7 19
Diam Slot size Set from ft. to ft.	Date well drilling machine moved off of well	1/11	19
(9) CONSTRUCTION:	(13) PUMP:		
	(10) 1 0.1.21		
Well seal—Material used in seal	Manufacturer's Name	*************	
Depth of seal ft. Was a packer used?	Type:	H.P	-
Diameter of well bore to bottom of seal	Water Well Contractor's Certification:		
Were any loose strata cemented off? ☐ Yes ☐ No Depth		سائماله المحدد	
Was a drive shoe used? ☐ Yes ☐ No	This well was drilled under my jurisdiction true to the best of my knowledge and belief.	and this	report is
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	Miller Desire		
Gravel placed from ft. to ft.	NAME (Person, firm or corporation) (T)	<i>U /≡ S'7</i> ype or prin	t)
Did any strata contain unusable water? Yes	Address 5545 dosepH ST	SIE	SALREM
Type of water? depth of strata	1 (1)		
Method of sealing strata off	Drilling Machine Operator's License No	<u>x</u>	•••••
(10) WATER LEVELS:	rained the la Popular	i o	
Static level ft. below land surface Date 3/7/67	[Signed] (Water Well Contractor)	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	
Artesian procesure the ner square inch Date	Contractor's License No. 37 Date 3/2	167	19

STATE ENGINEER Salem, Oregon

State Well No.	10/2W-29M(1)
County	Linn
Application No.	GR-196

Well Log

Owner: Frank W. Groves				
Driller:				
CHARACTER OF MATERIAL	(Feet below From		Thickness (feet)	
Soil	0	5	5	
Gravel	5	8	3	
Sand & soil	8	12	4	
Sand & gravel	12	19	7	
To.				
· · · · · · · · · · · · · · · · · · ·				
	·			