ORIGINAL GERVEWATER WE	LL REPORT 1 100 State Well No. G-608 2w -29 C
File Original and Duplicate with the STATE ENGINEER, SALEM, OREGON	· 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
(1) OWNER:	(11) WELL TESTS: Dráwdown is amount water level is lowered below static level
(1) OWNER: Name Paul R. and June E. Smith	Was a pump test made? ☐ Yes ☐ No If yes, by whom?
Address Rt. 2 Box 500 Albany, Ore.	Yield: gal./min. with ft. drawdown after hrs.
	" "
	22 23 23
(2) LOCATION OF WELL:	Bailer test gal./min. with ft. drawdown after hrs.
County Linn Owner's number, if any— # 2	Artesian flow g.p.m. Date
SW SE 1/4 Section 29 T. 10S R. 2 W. W.M.	Temperature of water Was a chemical analysis made? Yes X No
Bearing and distance from section or subdivision corner	(10) WILL TOO 8
N. 60° 30' W. 26.3 chains from the SE	(12) WELL LOG: Diameter of well8 inches.
corner of S. 29, T. 10 S., R. 2 W.W.M.	Depth drilled 21 ft. Depth of completed well 21 ft.
The state of the s	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each
The second secon	stratum penetrated, with at least one entry for each change of formation.
	MATERIAL FROM TO
TYPE OF WORK (check):	Sandy clay, brown 0 12
New Well Deepening Reconditioning Abandon Abandon	Water bearing sand & gravel, brown 12 21
If abandonment, describe material and procedure in Item 11.	
PROPOSED USE (check): (5) TYPE OF WELL:	
mestic Industrial Municipal Rotary Driven Cable M Jetted	
Trigation ☐ Test Well ☐ Other ☐ Dug ☐ Bored ☐	
(6) CASING INSTALLED: Threaded Welded	
8 "Diam. from 0 ft. to 21 ft. Gage 280	
ft. to ft. Gage	
(7) PERFORATIONS: Perforated? ☑ Yes ☐ No	
Type of perforator used Cutting torch	
SIZE of perforations 3/8 in. by 7 in.	
18 perforations from 14 ft. to 21 ft.	
perforations from ft. to ft.	
perforations from	
perforations from ft. to ft.	
perforations from ft. to ft.	·
SCREENS: Well screen installed Yes No	
anufacturer's Name	
Type Model No.	
Diam. Slot size Set from ft. to ft. to ft.	Work started April 19 19 57. Completed April 22, 19 57
am Slot size Set from ft. to ft.	Work started April 19 19 57. Completed April 22, 19 57
ONSTRUCTION:	(13) PUMP:
Was well gravel packed? Yes X No Size of gravel:	Manufacturer's Name U.S. Pump Co.
Gravel placed from ft. to ft.	Type: centrifugal H.P. 15
Was a surface seal provided? ☐ Yes 🖾 No To what depth?	
Material used in seal—	Well Driller's Statement:
Did any strata contain unusable water? Yes X No	This well was drilled under my jurisdiction and this report is
Type of water? Depth of strata	true to the best of my knowledge and belief.
Method of sealing strata off	NAME William M. Slate (Person, firm, or corporation) (Type or print)
(10) WATED I EVELS.	
(10) WATER LEVELS: Static level 6 ft. below land surface Date 4/22/57	Address 1145 S. Geary St. Albany, Ore.
	Deilleute weell neuroben
Artesian pressure lbs. per square inch Date	Driller's well number
Log Accepted by:	[Signed] William M Slates
Isimod Road (1) and note AU 920 105	7 (Well Drifter)
[Signed] Jand Date Aug 20, 195	License No. 106 Date August 19, 1957
JUSE ADDITIONAL (USE ADDITIONAL	SHEETS IF NECESSARY)