NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

SEP 2 2 1972 STATE OF OREGON

WATER WELL REPORT
4469

State Well No. .

state engineer, salem, oregon 97310 EP 2 2 1972 STATE of oregon
within 30 days from the date ATE ENGINEER (Please type or print)
of well completion.

SALEM. OREGON write above this line) 6 6003

State Permit No. .

(1) OWNER:	(10) LOCATION OF WELL:
Name Vernon H. Hoefer	County Linn Driller's well number
Address Rt. 2, Box 199, Albany, Ore. 97321	14 14 Section 4 T. 1.OS R. 3W W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well 🔥 Deepening 🗆 Reconditioning 🗀 Abandon 🖂	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 23 ft.
Rotary	Static level 17 ft. below land surface. Date
Dug Bored I Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded K  10	(12) WELL LOG: Diameter of well below casing 10 <sup>11</sup>
"Diam, from ft. to ft. Gage	Depth drilled 36 ft. Depth of completed well 36 ft.
	Formation: Describe color, texture, grain size and structure of materials;
213	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Acetylene Torch  Size of perforations ½ in. by 12 in.	MATERIAL From To SWL
Size of perforations ½ in. by 12 in.  96 perforations from 23½ ft. to 35½ ft.	Top Soil 0 3
	Brown Sano 5 6
perforations fromft. toft.	Clay & Coarse Gravel 6 18 Dirty Gravel 18 22
perforations from ft. to ft.	
(7) SCREENS: Well screen installed? ☐ Yes 🐧 No	Brown Sand & Gravel 22 35 Brown Clay & Gravel 35 36
Manufacturer's Name	Drown Olay & Gravel 199 90
Type Model No	
Diam, Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	1.50
Was a pump test made? ☐ Yes ☐ Yoo If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" " "	
" " "	
Bailer test 100 gal./min. with NO ft. drawdown after 1½ hrs.	· · · · · · · · · · · · · · · · · · ·
Artesian flow g.p.m.	
Temperature of water Depth artesian flow encountered ft.	Work started 8_22 19 72 Completed 8_24 19 72
(9) CONSTRUCTION:	Date well drilling machine moved off of well 8-24 19 72
Well seal—Material usedBentonite	Drilling Machine Operator's Certification:
Well sealed from land surface to 18 ft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below sealin.	[Signed] Date 25, 1972 (Drilling Machine Operator)
Number of sacks of cement used in well seal sacks	
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 436
Brand name of bentonite Oregon Bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of waterlbs./190 gals.	true to the best of my knowledge and belief.
Was a drive shoe used? K Yes No Plugs Size: location ft.	Name Merle Warren Well Drilling (Persog, firm or corporation) (Type or print)
Did any strata contain unusable water?   Yes   No  Type of water?	Address Rt. 1) Box 84, Tangent, Ore, 97389
Type of water? depth of strata	Address Ave to To Total City Of Co 7/309
Method of sealing strata off	[Signed] Ifflee Warren
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No Date 19/