NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

LINN WATER WELL REPORTOC [3 1 1972

STATE OF OREGONATE ENGINEER Well No. (Please type or print) SALEM. OREGON State Permit No.

STATE ENGINEER, SALEM, OREGON 97310 WH 99 within 30 days from the date of well completion.

-		- '-	ب بودا براش	
	/Do not p	vrite above	this line)	
	(DO HOD !	TAREC MIDOTO	MILES 11110)	

(1) OWNER:	(10) LOCATION OF WELL:			
Name David Harnisch	County Linn Driller's well nu	mber		
Address Rt. 2, Box 201, Albany, Ore. 97321	34 % Section 5 T. 10S	R. 3W W.M.		
7 7 7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Bearing and distance from section or subdivision	on corner		
(2) TYPE OF WORK (check):				
New Well Deepening Reconditioning Abandon				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	-137 - 1 -11.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 24 ft.			
Deliver Cl.				
Cable Jetted   Domestic A industrial   Municipal	75	urface. Date 10-12-72		
Dug	Artesian pressure Ibs. per squar	e inch. Date		
CASING INSTALLED:   Threaded   Welded	(12) WELL LOG: Diameter of well below casing			
Type of perforator used Acetylene Torch	MATERIAL	From To SWL		
Size of perforations ½ in. by 12 in.	Top Soil	0 1		
110 96 perforations from 20'03" ft. to 32'03" ft.	Sand & Gravel	1 20		
perforations from ft. to ft.	Washed Brown Sand & Grav.	20 32		
perforations from ft. to ft.	Brown Clay & Gravel	32 33		
		-		
(7) SCREENS: Well screen installed?   Yes X No				
Manufacturer's Name				
Type Model No	***************************************			
Diam. Slot size Set from ft. to ft.	+ ''			
Diam. Slot size Set from ft. to ft.	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? 🛣 Yes 🔲 No If yes, by whom? Self				
Yield: 625 gal./min. with 25 ft. drawdown after 2½ hrs.	The state of the s			
gar, min. with it drawdown dret	The second secon			
" " "				
	The state of the s			
Bailer test gal./min. with ft. drawdown after hrs.	<u> </u>			
Artesian flow g.p.m.	70.0	ed 10-12 1972		
perature of water Depth artesian flow encounteredft.	Work started 10-9 19 72 Complet			
(9) CONSTRUCTION:	Date well drilling machine moved off of well	*		
Well seal—Material used Bentonite  Well sealed from land surface to 18 ft.  Diameter of well bore to bottom of seal 14 in.  Diameter of well bore below seal 10 in.  Number of wells of compart weed in well seal seals are seals of compart weed in well seals and information reported above are true to my best knowledge and belief.  [Signed]  Drilling Machine Operator's Certification:  This well was constructed under my direct supervision.  Materials used and information reported above are true to my best knowledge and belief.  [Signed]  Drilling Machine Operator's Certification:  This well was constructed under my direct supervision.  Materials used and information reported above are true to my best knowledge and belief.  [Signed]				
Diameter of well bore below seal10 in.	[Signed] (Drilling Machine Operator)	wate //		
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No.	436		
Number of sacks of bentonite used in well seal4sacks				
Brand name of bentonite Oregon Bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is			
Was a drive shoe used? XYes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.			
Did any strata contain unusable water?   Yes X No	Name Merle Warren Well Drilling (Type or print)			
Type of water? depth of strata	Address Rt. Box 84. Tange	nt. Ore. 97389		
Method of sealing strata off	Muse - Was	11		
Was well gravel packed? ☐ Yes 🛣 No Size of gravel:	[Signed] (Water Well Cont			
Gravel placed fromft. toft.	Contractor's License No182 Date	10-23,1977		