File Original and First Copy with the STATE ENGINEER,

STATE ENGINEER

WATER WELL REPORT

State Well No.

10/3W-6P

STATE OF OREGON

State Permit No.

SALEM, OREGON SALEM, OREGON	1 196019	
(1) OWNER;	(11) WELL TESTS: Drawdown is amount water level lowered below static level	el is
Name L, D, COOK,	Was a pump test made? Yes No If yes, by whom?	ullu
Address Rt to 2 130 X 7 147	Yield: 600 gal./min. with ft. drawdown after	2 hrs.
Albany Oregon	2) 9)	**
(2) LOCATION OF WELL:	n n	······
County A / M / Owner's number, if any—	Bailer test gal./min. with ft. drawdown after	hrs.
SE 14 SW 14 Section G T. 10 S R. ZW W.M.	Artesian flow g.p.m. Date	. <u>U</u>
Bearing and distance from section or subdivision corner	Temperature of water 🌮 / Was a chemical analysis made? 🔲	Yes X No
S 130 45' E. 255 CHAINS FROM	(12) WELL LOG: (Diameter of well	inches.
NW CORNER OF JOHN B. MILLER D.L.C		3/s.
12, t./05, R.3W.	Formation: Describe by color, character, size of material and str show thickness of aquifers and the kind and nature of the mater	ucture, and
	show thickness of aquifers and the kind and nature of the mater stratum penetrated, with at least one entry for each change of	formation.
	MATERIAL FROM	то
(9) MYDE OF WORK (sheets).	Surface + Chay Tob	12
(3) TYPE OF WORK (check): Now well Deepening T Reconditioning T Abandon D	10 24 Ba 3 1/4 1 TC 1 4 104 10	19
New Well Deepening □ Reconditioning □ Abandon □ If abandonment, describe material and procedure in Item 11.	Mixed Sin an aucerdant 14	22
it analidominent, describe material and procedure in 2001.	med hasses 11 Sanet	
PROPOSED USE (check): (5) TYPE OF WELL:	12145 22	31
Domestic Industrial Municipal Rotary Driven		
Irrigation Test Well Other Cable Jetted Dug Bored		
(6) CASING INSTALLED: Threaded Welded		
10 " Diam. from 10 tt. to 31 ft. Gage 230		
" Diam. from ft. to ft. Gage	•	
" Diam. from ft. to ft. Gage	•	
(7) PERFORATIONS: , Perforated? Yes No		
Plane		
Type of perforator used VACIS		
SIZE of perforations / in. by in.		
	· ——	
perforations from		
perforations from ft. to ft. t		
perforations fromft. toft		
(8) SCREENS: Well screen installed		_
Manufacturer's Name	.	
Type Model No.	.	
Diemin Slot size Set from ft. to ft.		1
D. Slot size Set from ft. to ft.	Work started Fell 27 18 Completed M34ch	8 194
	(40) DITTE	
(9) CONSTRUCTION:	(13) PUMP:	
Was well gravel packed? Yes No Size of gravel:	Manufacturer's Name FAIRBANKS MORSE	
Gravel placed from	Type: CENTRIFUGAL H.P.	/
Was a surface seal provided? Yes No To what depth? f		
Material used in seal— Did any strata contain unusable water? ☐ Yes ☐ No	Well Driller's Statement:	s report is
- A Live	This well was drilled under my jurisdiction and this true to the best of my knowledge and belief.	a rehore 12
1,500 02 Wallott, 7,17,57	How Brilling Co.	
Method of sealing strata off	NAME / Posson, firm, or corporation (Type or p)	rint)
(10) WATER LEVELS:	Albania Ilmania	
Static level / ft. below land surface Date 3 - 8 - 4	Address Address	
Artesian pressure lbs. per square inch Date	Driller's well number	
	Dill Hamilton)
Log Accepted by:	[Signed] (Well Driller). 700	
[Signed] D. L. Cook Date March 20 196	52 Wen Driver March 1	10 10%
(Owner)	License No. Date	, 1964!