	VC LINN 5085			
NOTICE TO WATER WELL CONFIDENCE OF EIVED The original and first confidence of this report are to be JUN 16 1965WATER WE filled with the				-
filed with the JOIN I O RECON 97312 INGINE STATE OF within 30 days from the Dite ATE INGINE STATE OF well completion.	F OREGON be or print)	State Well No.	36-	<u></u>
(1) OWNER:	(11) WELL TESTS:	Drawdown is amount v lowered below static le	vater level	is
Name Clover Ridge School	Was a pump test made? 🗌 Yes			
Address Clover Ridge Road	Yield: gal./min. with ft. drawdown after hrs.			hrs.
Albany, Oregon	11 11 11 11 11 11 11 11 11 11 11 11 11		37	
(2) LOCATION OF WELL:				
County Linn Driller's well number		. with 20 ft. drawdo	wn after	L hrs.
1/4 1/4 Section 27 T. 10S R. 3W W.M.	Artesian flow Temperature of water W	g.p.m. Date 'as a chemical analysis r	nade? [] V	es fit No
Bearing and distance from section or subdivision corner		·		811
- -		iameter of well below ca	using	
		Depth of completed we		<u>. ft.</u>
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifiers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.			
	MATERIA	AL	FROM	TO
(3) TYPE OF WORK (check):	Top :	Soil	0	3
Well 🕅 Deepening 🗌 Reconditioning 🗍 Abandon 🗍	Clay		3	18
Pabandonment, describe material and procedure in Item 12.		& Gravel	18	28
(4) PROPOSED USE (check): (5) TYPE OF WELL:		y Clay	28	36
Domestic 🔏 Industrial 🗌 Municipal 🔲 Rotary 🗌 Driven 🗌		& Gravel	<u> </u>	48
rrigation Test Well Other Dug Bored	B_ue	Clay	48	61
(6) CASING INSTALLED: Threaded [] Welded []	·····			·
	<u></u>			
	l.±	· · · · · · · · · · · · · · · · · · ·		
" Diam. from ft. to ft. Gage				
(7) PERFORATIONS: Perforated? X Yes D No				
Type of perforator used Acetylene Torch		-		
Size of perforations 3/16 in. by 12 in. 18 perforations from 43.106.11 ft. to 52.106.11 ft.		· · · · · · · · · · · · · · · · · · ·		
perforations from				
perforations from ft. to ft.				
perforations from ft. to ft.				<u> </u>
perforations from ft. to ft.				
(8) SCREENS: Well screen installed? Yes X No				
Manufacturer's Name	· · · · · · · · · · · · · · · · · · ·	•	,	
Manufacturer's Name		· · · · · · · · · · · · · · · · · · ·		
Dram,	Work started 6-9	1965. Completed 6	10	1065
Diam Slot size Set from ft. to ft.	Date well drilling machine mov		-10	¹⁹ 65 ¹⁹ 65
(9) CONSTRUCTION:	(13) PUMP:		<u> </u>	
Well seal-Material used in sealBentonite	Manufacturer's Name			
Depth of seal	Туре:			
Diameter of well bore to bottom of seal	Water Well Contractor's Certification:			
Were any loose strata cemented off? [] Yes X No Depth				
Was a drive shoe used? 🛣 Yes 📋 No Was well gravel packed? 🗖 Yes 🌋 No Size of gravel:	This well was drilled un true to the best of my know	nder my jurisdiction a vledge and belief.	and this :	report is
Gravel placed from ft. to	Menle Won	nen Woll Drill	ing	
Did any strata contain unusuable water? 🔲 Yes 🏼 🛣 No	NAME Merle Warren Well Drilling (Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address			
Method of sealing strata off	* .	+ · · · ·		
(10) WATER LEVELS:	Drilling Machine Operator	محطر شب الججر	ren	
Static level 25 ft. below land surface Date 6-10-65	[Signed]	(Water Well Contractor)	A	<u> </u>
Artesian pressure Ibs. per square inch_Date	Contractor's License No	182 Date - 🧭 🖊	70	, 19 6)
(USE ADDITIONAL S	IEETS IF NECESSARY)			sur e s