## WATER WELL REPORT STATE OF OREGON

LINN 50854 -/NN MAY 7 1981

WATER RESOURCES DEPT SALEM, OREGON

State Well No.	25/3W-34 bes
State Permit No.	6-9139

1) OWNER:	(10) LOCATION OF WELL:		
John Koos & Sons	County Linn Driller's well	number 162-2	<u>-81</u>
Address 30929 Seven Mile Ln.	SE 4 NW 4 Section 34 T. 12S	R. 3W	W.M.
sity Albany, Tangent, State Ore.	Tax Lot # Lot Blk	Subdivision	
		Mile Ln.	
2) TYPE OF WORK (check):	Tangent, Or	<u>e.</u>	
New Well X Deepening □ Reconditioning □ Abandon □	(11) WATER LEVEL: Completed w	ell.	
f abandonment, describe material and procedure in Item 12.	Depth at which water was first found	40	ft.
3) TYPE OF WELL: (4) PROPOSED USE (check):		and surface. Date	
lotary Air	<u> </u>	er square inch. Date	
ry Mud  Dug  Irrigation  Test Well  Other	(12) WELL LOG: Diameter of well below	. 10	
Bored   Thermal: Withdrawal Reinjection			30 ft.
5) CASING INSTALLED: Steel X Plastic	Depth drilled 23() ft. Depth of Formation: Describe color, texture, grain size and structure,	<del>-</del>	<del></del>
12 Threaded Welded X	thickness and nature of each stratum and aquifer pene	trated, with at least	one entry
	for each change of formation. Report each change in and indicate principal water-bearing strata.	osition of Static Wa	ter Level
" Diam. from		<del> </del>	
LINER INSTALLED:	MATERIAL	From To	SWL
	top soil	0 3	
) PERFORATIONS: Perforated? X Yes \( \square\) No	<u>çlay brown</u>	3 20	
Type of perforator used	clay brown sandy	20 38	
Size of perforations in. by 4 in.	gravel + black sand	38 50	
1,600+ perforations from 30 ft. to 195 ft.	sand + blue clay	50 58	
perforations from	sand black and clay	58 80	
perforations from	gravel + black sand	80 110	
	sand brown + clay	110 150	
(7) SCREENS: Well screen installed?   Yes   No	clay blue hard	150 160	
Manufacturer's Name	black sand + clay	160 185	
Type Model No	sand brown + clay	185 200	
Diam. Slot Size Set from ft. to ft.	clay black + sandy	205 220	
Diam. Slot Size Set from ft. to ft.  Drawdown is amount water level is lowered	clay brown hard sandy	220 230	
(8) WELL TESTS:  Drawdown is amount water level is lowered below static level		<del>                                     </del>	
a pump test made? A Yes I No If yes, by whom? OWNEY		<del>                                     </del>	
a pump test made. 25 Tes 2 Tes 4 4 0		<del>                                     </del>	
gal./min. with 140ft. drawdown after 12 hrs.		<del>                                     </del>	
ctest gal./min. with drill stem at ft. hrs.		<del>                                     </del>	
1 250			
Bailer test gal./min. with it. drawdown after nrs.  esian flow g.p.m.		<del>                                      </del>	
1 comperature of water 52 Depth artesian flow encountered ft.	Work started 2/9 19 81 Complet	ed 4/9	198
	Work started 2/9 19 Complet  Date well drilling machine moved off of well	4/9	198
) CONSTRUCTION: Special standards: Yes □ NoX□ Well seal—Material used Cement	<del></del>		
20	Drilling Machine Operator's Certification:		مامات
well sealed from land surface to	This well was constructed under my direct and information reported above are true to my	oest knowledge an	d belief.
Diameter of wen sore to section of section of	[Signed] Bot Schiller	Date .4,7.20	
O.O.	(Drilling Machine Operator)	-	
Number of sacks of centent used in wen sear	Drilling Machine Operator's License No	. <del>9</del> .10	
How was cement grout placed?  6 gal. water per bag cement	Water Well Contractor's Certification:		
injected down grout hole	This well was drilled under my jurisdictio	n and this report	is true to
Was pump installed?	the best of my knowledge and belief.	2772	
Was a drive shoe used?	Name Bob Scheler Well Dr.	TTATA	print)
Did any strata contain unusable water?  Yes X No	Address 405 N Burkhart A	lbany, Ord	⊋.•
Type of Water? depth of strata	Red Jakobs -	• • • • • • • • • • • • • • • • • • • •	
Method of sealing strata off	[Signed] (Water Well Contra	ctor)	
Was well gravel packed? X Yes □ No Size of gravel: 2 X 3 /4	Contractor's License No. 610 Date	4/20	<b>, <sub>198</sub></b> .
Gravel placed from			·