STATE ENGINEER TATE ENGINE	WATER WELL DRIL ER STATE OF OR	LLERS REPORT Do Not State Well No. 346(1) REGON State Permit No. 346(1)
(1) OWNER: SALEM, OREGON		(10) WELL TESTS: Williamette
Name Harvey E. Brenneman		Was a pump test made?
Address Rt. 2 Box 519 Albany, Ore.		Yield: 200 gal./min. with 95 ft. draw down after 5 hrs.
		n n
(2) LOCATION OF WELL:		Artesian flowg.p.m.
County Linn Owner's number, if any 57		Shut-in pressurelbs. per square inch.
R. F. D. or Street No. Rt. 2 Albany, Ore.		Bailer test g.p.m. with ft. drawdown
Bearing and distance from section or subdivisio		Temperature of water 400 West a charies
360 101.7.01 chains from NE corner of D.L.C 43,		Was electric log made of well? Yes No
T. 10 S., R. 3 WWM., being within the SW of NE of Sec. 34, Twp. 10 S, R 3 W.W.M. County		
of in		(11) WELL LOG:
(5) TYPE OF WORK (check):		Diameter of well,8 inches.
New well Deepening Reconditioning Abandon		Total depth 126 ft. Depth of completed well 126 ft.
If abandonment, describe material and procedure in Item 11.		Formation: Describe by color, character, size of material and structure, and
		Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
PROPOSED USE (check):	(5) EQUIPMENT:	O ft. to 18 ft. gray & brown clay
i stic □ Industrial □ Municipal □		18 " 19 " blue clay
Irrigation M Test Well Other	Cable X	19 " 25 " gravel cemented with brown clay
	Dug Well	25 " 26 " water gravel medium
(6) CASING INSTALLED:	If gravel packed	26 " 35 " gravel cemented with brown clay
Threaded □ Welded □	- -	35 " 36 " water gravel medium to large
Gage or	Diameter from to	
"O717" "O 5 70 200"	of Bore ft. ft.	45 " 46 " water gravel & sand medium
<u>"97'3" "8 5/8 .280"</u>	" "	46 " 53 " gravel cemented with brown clay
22 22 32 33 33 33 33 33 33 33 33 33 33 3	22 22	53 " 55 " water gravel & sand small
31 22 29 35 29	22 21	55 " 62 " gravel cemented with brown clay
27 27 27 27 25	22 22	62 " 64 " water gravel small to large
Type and size of shoe or well ring stee]	Size of gravel:	64 " 67 " gravel cemented with blue clay
Describe joint welded		67 " 68 " blue clay
		68 " 70 " gravel cemented with blue clay
(7) PERFORATIONS:		70 " 71 " water gravel black small amount
Type of perforator used Mills Casin		71 " 113 " gravel cemented with blue clay
	length, by $5/16$ in.	113 " 119 " sandy blue clay
- 60 60 10	per foot No. of rows	119 " 126 " blue clay
<u> 35 36 24</u>	4 " "	"
45 46 24	4 " " " "	"
53 55 24	<u> 4 </u>	D D
62 64 30	5	"
SCREENS: 71 24	4	"
Give Manufacturer's Name, Model No.	and Size	"
		" "
(8) CONSTRUCTION:		" "
Was a surface sanitary seal provided? Yes		"
Were any strata sealed against pollution? \square Ye If yes, note depth of strata	es XNo	Ground elevation at well site feet above mean sea level.
FROM ft. to	ft.	Work started 17/28/55 19 , Completed 1/23/56 19
2)	29	Well Driller's Statement:
MEMILOD OF CEAL DIG		This well was drilled under my jurisdiction and this report is
METHOD OF SEALING true		true to the best of my knowledge and belief.
(9) WATER LEVELS:		NAME Wm. M. Slate
Depth at which water was first found 25 ft.		(Person, firm, or corporation) (Typed or printed)
Standing level before perforating 4	ft.	Address Tangent Ore.
Standing level after perforating	ft.	Driller's well number
Tog Accounted by:		
<i>4 :</i> /7 ·/\	1, 2-14 1956	[Signed] (Well Driller)
Owner Owner	1920	License No. 106 Dated 2/11 19 56
V		