

The original and first copy of this report are to be filed with the

RECEIVED STATE ENGINEER SALEM, OREGON JAN 18 1971

WATER WELL REPORT

STATE OF OREGON (Please type or print)

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

State Well No. 10/3W-34ac State Permit No. 5263

(1) OWNER:

Name ASGAR Sadri Address HCL W-83 ALBANY ORE

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven [] Cable [X] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [X] Irrigation [] Test Well [] Other []

CASING INSTALLED:

8" Diam. from 2 ft. to 11.9 ft. Gage 250

PERFORATIONS:

Type of perforator used MILLS CASING KNIFE Size of perforations 3/16 in. by 3 in. 19 perforations from 6.5 ft. to 7.2 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [] No Yield: gal./min. with ft. drawdown after hrs. Bailer test 60 gal./min. with 10 ft. drawdown after 2 hrs. Artesian flow g.p.m. Temperature of water 54 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used CEMENT GROUT Well sealed from land surface to 22 ft. Diameter of well bore to bottom of seal 16 in. Diameter of well bore below seal 8 in. Number of sacks of cement used in well seal 16 sacks Number of sacks of bentonite used in well seal Brand name of bentonite Number of pounds of bentonite per 100 gallons of water Was a drive shoe used? [X] Yes [] No Plugs Size: location ft. Did any strata contain unusable water? [] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County LINN Driller's well number 1/4 1/4 Section 34 T. 10S R. 3W W.M. Bearing and distance from section or subdivision corner 20' SOUTH OF WELL AT 46° 10' 7.01 CHAINS FROM NE CORNER OF D.S. 43

(11) WATER LEVEL: Completed well.

Depth at which water was first found ft. Static level 5 ft. below land surface. Date 12-20-70 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8" Depth drilled 122 ft. Depth of completed well 122 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include: TOPSOIL, GRAY CLAY, BROWN CLAY w/ SAND + GRAVEL, YELLOW CLAY w/ SAND, SAND GRAVEL + WATER, YELLOW CLAY, SAND GRAVEL, YELLOW CLAY + SAND, SAND GRAVEL + WATER, YELLOW CLAY SAND + GRAVEL, BLUE CLAY + SAND, BLACK SAND GRAVEL + WATER, BLUE CLAY, BLUE CLAY w/ BLACK SAND, SAND GRAVEL + WATER.

Work started 11-18 1970 Completed 12-20 1970 Date well drilling machine moved off of well 12-22 1970

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Leeman A. White Date 1-12, 1971 (Drilling Machine Operator) Drilling Machine Operator's License No. 554

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name BOBS WALL DRILLING (Type or print) Address 465 WAGON WHEEL D.R. LE BANON (Type or print) [Signed] Robert White (Water Well Contractor) Contractor's License No. 121 Date 1-15, 1971