LINN 53286

## STATE OF OREGON

WATER SUPPLY WELL REPORT
(as required by ORS 537.765)
Instructions for completing this report are on the last page of this form

WELL ID # L 39405

(START CARD) # 134070

(1) OWNER: Well Number: 39405	(9) LOCATION OF WELL by legal description	on: Longitude	9	
Name Johnson's Park and Water Co.	Township 9/S Nor S. Range 3/E	E or W. of W		
Address 51037 Greenway Drive City Gates State OR Zip 97346		Section 25 SE 1/4 ST Tax lot 109 Lot Block	SW 1 Subdivision	/4
		Street Address of Well (or nearest address) Same		
(2) TYPE OF WORK:  X New Well Deepening Alteration (repair/recondition)	andonment			
Version of the control of the contro		(10) STATIC WATER LEVEL:	D.1	
(3) DRILL METHOD:		22 ft. below land surface.  Artesian pressure lb. per square inch	Date <u>8/1(</u> h. Date	
X Rotary Air     □ Rotary Mud     □ Cable     □ Auger       □ Other     □ Other				
(4) PROPOSED USE:		(11) WATER BEARING ZONES:  Depth at which water was first found 30		
Domestic X Community Industrial Irrigat	ion	Depth at Which Water was hist found 30		1
Thermal Injection Livestock Other		1,010	nated Flow Rate	SWL 22
(5) BORE HOLE CONSTRUCTION:		30 40 53	11.5	22
Special Construction approval Yes XNo Depth of Completed We	ell <u>60</u> ft.			
Explosives used Yes XNo Type Amount	mount			1
HULE SEAL	or pounds	(12) WELL LOG:  Ground elevation		
11.25 0 19 Bentonite 0 7 4 Sks				1
11.25 0 19 Cement 7 19 6 Sks 7.5 19 60	·	Material Topsoil	From To	SWL
7.5		Clay brown silty	5 10	
		Basalt boulder dark grey hard w/jagged seams	10	
How was seal placed: Method A B XC D E		Cobbels & gravel multi-color	15	
X Other Poured & probed		large to med	28 53	
Backfill placed from         ft. to         ft.         Material           Gravel placed from         ft. to         ft.         Size of gravel		Gravel multi-color med to small Sandstone grey fractured	53 60	
(6) CASING/LINER:				4
Casing: Casing: To Gauge Steel Plastic Welded X	Threaded			
		The state of the s		
Liner:		There wet to me		
Final location of shoe(s) 59' U.R. Shoe		AUC : 0 2000		
(7) PERFORATIONS/SCREENS:	AUG 1 % 7000			
Perforations Method Open bottom		WATERESOUNCES (NEW)		
Screens Type Material		SALLIM, CREGON		
Slot Tele/pipe From To size Number Diameter size Casing	Liner			
FIOII 10 Size (Valido) Blancier Size Stand				
		Date started 8/10/2000 Completed 8	3/10/2000	
		(unbonded) Water Well Constructor Certificatio	n:	
		I certify that the work I performed on the construction, all of this well is in compliance with Oregon water supply we	Iteration, or aband Ill construction sta	ionment Indards.
(8) WELL TESTS: Minimum testing time is 1 hour		Materials used and information reported above are true to	my best knowled	lge and
□ Pump □ Bailer ☒ Air □ Flowi	ng Artesian	belief.	/WC Number 17	25
Yield gal/min Drawdown Drill stem at Ti	me	Signed Ovor Lukennows Di	ate 8/16/2000	
11.5 55 1 hi	7.	Mack Drilling Company, Inc.		
		(bonded) Water Well Constructor Certification:	or abandonment v	vork
I accept responsibility for the construction, alteration, or abandonment work performed on this well during the construction dates reported above. All work				
Temperature of Water 57 Depth Artesian Flow found performed during this time is in compliance with Oregon water supply well				
Was a water analysis done? Yes By whom Did any strata contain water not suitable for intended use? Too little	T / / /////	/We Number 13	94	
Salty Muddy Odor Colored Other Signed Liquid Website 8/16/2000				
Depth of strata:		Mack Drilling Company, Inc.		