

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

LINN 54150
WATER WELL REPORT

STATE OF OREGON
(Please type or print)

State Well No. 12S/3W-7
State Permit No.

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

(Do not write above this line)

(1) OWNER:

Name Pickseed West
Address 3523 S. Pacific Blvd., Albany, Ore.
97321

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded
8" Diam. from +1.03 ft. to 84.04 ft. Gage 250 Wall
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.
Type of perforator used Acetylene Torch
Size of perforations 1/2 in. by 12 in.
54 perforations from 73 ft. to 84 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " " "
" " " " " "
Bailer test 110 gal./min. with 6 1/2 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Bentonite
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal 3 sacks
Brand name of bentonite Oregon Bentonite
Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Linn Driller's well number
1/4 Section 7 T. 12S R. 3W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 28 ft.
Static level 9 1/2 ft. below land surface. Date 6-8-73
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8"
Depth drilled 85 ft. Depth of completed well 85 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Rock Fill	0	2	
Top Soil	2	4	
Brown Clay	4	17	
Brown Clay & Gravel	17	28	
Dirty Gravel	28	31	
Brown Sand & Gravel	31	37	
Brown Clay & Gravel	37	48	
Blue Clay & Gravel	48	55	
Packed Black Sand	55	68	
Black Sand & Sm. Gravel	68	85	

Work started 6-5 19 73 Completed 6-8 19 73
Date well drilling machine moved off of well 6-8 19 73

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Walter Warren Date 7/6, 19 73
(Drilling Machine Operator)
Drilling Machine Operator's License No. 436

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Merle Warren Well Drilling
(Person, firm or corporation) (Type or print)
Address Rt. 1, Box 84, Tangent, Ore. 97389
[Signed] Merle Warren
(Water Well Contractor)
Contractor's License No. 182 Date 7/6, 19 73