NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

LINN 54239

N NWATER WELL SEPORT WELL 24 1973

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(Please type or print) Eate Permit No. (Do not write above this line) 1 (14)

(1) OWNER:	(10) LOCATION OF WELL:	
Name Plainview Mennonite Church	County Linn Driller's well number	
Address % Millard Paulus, Rt. 1, Box 199	14 14 Section 35 T. 12S	R. 3W W.M.
	Bearing and distance from section or subdivisi-	on corner
(2) TYPE OF WORK (check):		
New Well M Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	
(3) TYPE OF WELL: (4) PROPOSED USE (check):		
	Depth at which water was first found	25 ft.
Cable Domestic Industrial Municipal	Static level 7 ft. below land s	urface. Date 6-22-73
Dug	Artesian pressure lbs. per squar	e inch. Date
(a) CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well h	
6" Diam. from -12" ft. to 100.051/21. Gage17#	Diameter of ven select culture	
	Depth drilled 110 ft. Depth of completed well 110 ft.  Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,	
" Diam. from ft. to ft. Gage		
	with at least one entry for each change of format	tion. Report each change in
Perforated? Y Yes \( \square\) No.	position of Static Water Level and indicate prin	cipal water-bearing strata.
vpe of perforator used Acetylene Torch	MATERIAL	From To SWL
Lize of perforations 3/8 in. by 12 in.	Top Soil	0 2
	Brown Clay	2 13
perforations from ft. to ft.	Brown Clay & Gravel	13 19
perforations from ft. to ft.	Brown Sand & Gravel	19 26
(7) SCDEENS.	Packed Brown Sand	26 35
(7) SCREENS: Well screen installed? ☐ Yes No	Yellow Clay	35 55
Manufacturer's Name	Reddish Brown Clay	55 67
Type         Model No.           Diam.         Slot size         Set from         ft. to         ft.	Blue Clay	67 85
Diam. Slot size Set from ft. to ft.	Black Clay	85 92
Diam. Slot size Set from 1t. to	Blue Clay & Dk Blue Slate	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Black Clay	108   110
Was a pump test made? Yes No If yes, by whom?		
d: gal./min. with ft. drawdown after hrs.		
" " "		
" " "		
Bailer test 30 gal./min. with 83 ft. drawdown after 1 hrs.		
^ tesian flow g.p.m.		
nperature of water Depth artesian flow encountered ft.	Work started 6-19 19 73 Complete	ed 6-22 19 73
A CONCERNICATION	Date well drilling machine moved off of well	6 <b>-</b> 22 <sub>19</sub> 73
) CONSTRUCTION:		
Well seal—Material used Bentonite	Drilling Machine Operator's Certification: This well was constructed under my	direct supervision
Well sealed from land surface toft.	Materials used and information reported	
Diameter of well bore to bottom of seal in.	best knowledge and belief.	
Diameter of well bore below seal in.	[Signed] Date Date (Drilling Machine Operator)	
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No436	
Number of sacks of bentonite used in well seal sacks Brand name of bentonite Oregon Bentonite		
	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons of waterlbs./100 gals.	This well was drilled under my jurisdi	
or water	true to the best of my knowledge and bel	
Did any strata contain unusable water?   Yes No	Name Merle Warren Well Dri (Person, film or corporation)	(Type or print)
	Address Rt. 1, Box 84, Tange	
Type of water? depth of strata	M. 1	
Method of sealing strata off	[Signed]	arrey
Was well gravel packed? Tyes 🛣 No Size of gravel:	(Water Well Contr	6/3000
Gravel placed from ft. to ft.	Contractor's License No 182 Date	T / 19 /
(IISE ADDITIONAL SI	IPPTC IF NECECCADUL	SD+45656_110