## RECEIVEIN

54574

STATE OF OREGON OCT 19 2001 WATER SUPPLY WELL REPORT WELL I.D. # L\_49886 (as required by ORS 537.765) WATER RESOURCE
Instructions for completing this report are on the last rage of the (as required by ORS 537.765) START CARD # 141658 (1) LAND OWNER Well Number (9) LOCATION OF WELL by legal description: County <u>Linn</u> Name Gary Roth \_Latitude\_ \_Longitude . 34054 Seven Mile Address 11 S Township N or S Range Albany OR SW SW Section\_ 1/4 (2) TYPE OF WORK Tax Lot 500 Lot \_Block \_ Subdivision \_ New Well Deepening Alteration (repair/recondition) Abandonment Street Address of Well (or nearest address)

33803 Seven Mile Ln - Albany (3) DRILL METHOD: ☐ Rotary Air ☐ Rotary Mud 【 Cable ☐ Auger (10) STATIC WATER LEVEL: Other. 19' \_\_\_ ft. below land surface. (4) PROPOSED USE: Artesian pressure \_\_\_ \_\_\_\_lb. per square inch ☐ Domestic ☐ Community ☐ Industrial X Irrigation (11) WATER BEARING ZONES: ☐ Thermal Injection ☐ Livestock ☐ Other\_ (5) BORE HOLE CONSTRUCTION: Depth at which water was first found \_ Special Construction approval Yes No Depth of Completed Well 226 From To **Estimated Flow Rate** SWL Explosives used Yes No Type\_ 20 44. 25gpm 13 HOLE **SEAL** Diameter From To Material From To Sacks or pounds 14" 0 50 50 cement <u> 30sacks</u> 10" 50 220 (12) WELL LOG: How was seal placed: Method  $\square A$  $\square$  B X C  $\square D$ Ground Elevation . □ Other Backfill placed from Material ft. to\_ Material From **SWL** Gravel placed from \_ Size of gravel Top soil 0 2 (6) CASING/LINER: Brown clay 2 19 Diameter Gauge Steel From Plastic Welded Threaded Brown clay&gravel 19 44 13 Casing: Brown clay 44 48 10" 1'06' 48 Gray clay 60 <u> 250</u> 🗶 X Black sand 60 65 Dark gray clay 65 80  $\Box$ П  $\Box$ П Liner: Black sand&gravel 80 105  $\Box$ Dark gray clay 105 120 Drive Shoe used Inside Outside None Black sand&gravel 120 130 Final location of shoe(s)\_ 189 Dark blue clay 130 138 (7) PERFORATIONS/SCREENS: Cemented sand& ▼ Perforations Method Acetylene torch 146 grave] 138 □ Screens Type Material Black sand&gravel 146 164 Slot Tele/pipe 19 From To Number Diameter size Casing Liner Dark gray clay 164 <u> 166</u> <u>Black sand & gravel</u> 188 128 189 80 10" X Firm dark gray clay 220 12" <u>.08"</u> (8) WELL TESTS: Minimum testing time is 1 hour Date started 9-6-0110-4-01 Completed Flowing (unbonded) Water Well Constructor Certification? ☐ Pump **X** Bailer □Air ☐ Artesian I certify that the work I performed on the construction, alteration, or abandon-Yield gal/min Drawdown Drill stem at Time ment of this well is in compliance with Oregon water supply well construction 120gpm 6 l hr. standards. Materials used and information reported above are true to the best of my knowledge and belief. WWC Number <u>53</u> (bonded) Water Well Constructor Certification: Temperature of water \_\_\_\_ \_Depth Artesian Flow Found I accept responsibility for the construction, alteration, or abandonment work Was a water analysis done? ☐ Yes By whom. performed on this well during the construction dates reported above. All work Did any strata contain water not suitable for intended use? performed during this time is in compliance with Oregon water supply well ☐ Salty ☐ Muddy ☐ Odor ☐ Colored ☐ Other \_ construction standards. This report is true to the best of my knowledge and belief. Depth of strata:. WWC Number Date 10-10-01