NOTICE TO WATER WELL CONTE The original and first copy of this i are to be filed with the

depth of strata

Size of gravel:

.... ft.

Type of water?

Gravel placed from

Method of sealing strata off

Was well gravel packed? 🗌 Yes 🗷 No

WATER RESOURCES DEPARTME SALEM, OREGON 97310 within 30 days from the date of well completion.

NN 54762 WATER WELL REPORT

•	Well	No.	125/4W	-38
	_		_	NHM

	noverthis line).	No	
(Woodland Park Mobile Hom	(10) LOCATION OF WELL:	d OK 10-12-78 AS	
(1) OWNER: (WOOdland Park Hobite hom	(40) LOCATION OF WELL:	0/17/	
Name Ella M.Gates	County Linn Driller's well	number S/43/k	
Address 33201Peoria Road		S_{R} . $4W_{W.M}$.	
Corvallis, Oregon 97330	Bearing and distance from section or subdivi	sion corner	
(2) TYPE OF WORK (check):			
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed	well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	42 ft.	
Rotary Driven Domestic Dindustrial Municipal	Static level 12 ft. below land	surface. Date 5/17/78	
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ♣	Artesian pressure lbs. per squa	are inch. Date	
CASING INSTALLED: Threaded □ Welded ■ 10 "Diam. from 0 ft. to 61 ft. Gage	(12) WELL LOG: Depth drilled Depth drilled Formation: Describe color, texture, grain size and show thickness and nature of each strat with at least one entry for each change of form position of Static Water Level and indicate prices.	pleted well ft. and structure of materials; um and aquifer penetrated, ation. Report each change in	
Type of perforator used Torch cut	MATERIAL	From To SWL	
Size of perforations 4 in. by 4 in.	Topsoil	0 1	
130 perforations from 46 ft. to 58 ft.	Brown sandy clay	1 12	
perforations fromft. toft.	Brown clay sandagravel	12 27	
perforations from ft. to ft.	Brown gravel	27 38	
	Black sand	38 42	
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	black gravel & Sand	42 58	
Manufacturer's Name	blue clay&black gravel	58 59	
Type Model No.	_blue clay	59 61	
Diam Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? Yes No If yes, by whom? Northwest?	Limp		
vield: 165 gal./min. with 20 ft. drawdown after 8 hrs.			
" " "			
n n			
The Manual Area Area Area Area Area Area Area Area			
Bailer test gal./min. with ft. drawdown after hrs.		 	
Artesian flow g.p.m.	- Ide Chara		
perature of water Depth artesian flow encountered ft.	Work started 5/16/78 19 Comple	ted 5/17/78 19	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	5/17/78 ¹⁹	
Well seal—Material used	Drilling Machine Operator's Certification		
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	airect supervision. l above are true to my	
Diameter of well bore to bottom of seal 14 in.	best knowledge and belief.		
Diameter of well bore below sear	[Signed] (Drilling Machine Operator)	Date5/22/7,819	
sacks of cement used in well seal	Drilling Machine Operator's License No		
How was cement grout placed? Pumped through tremie			
	Water Well Contractor's Certification:	11-41 411 ·	
	This well was drilled under my jurisd true to the best of my knowledge and be	neuon and this report is lief.	
Was a drive shoe used? Yes 📆 No Plugs Size: location ft.	Name Corvallis Drilling Co. J		
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Type or print)	

Address 3440 SW 3rd St. Corvallis, Oregon 97330

Contractor's License No. 560 Date 5/22/78 , 19

(Water Well Contractor)