LINN 57202

STATE OF OREGON WATER SUPPLY WELL REPORT

WELLID #L 84201

TER SOITET WEEE RELOKT	WELL I.D. # L
required by ORS 537.765)	START CARD# 18/620

Instructions for completing this report are on the last page of this form.	
(1) LAND OWNER Well Number 249/	(9) LOCATION OF WELL (legal description) County
Address 31595 Driver Rd.	Tax Lot Lot
City Tangent State OR Zip 97389	Township 135 N or Range 034 E or WM
(2) TYPE OF WORK New Well	Section <u>07</u> <u>// XE</u> 1/4 <u>NE</u> 1/4
Deepening Alteration (repair/recondition) Abandonment Conversion	Lat
	Long o ' " or (degrees or decimal)
(3) DRILL METHOD	Street Address of Well (or nearest address) Bosba Mills Rel.
Rotary Air Rotary Mud Cable Auger Cable Mud	Shedd, OC
Other	
(4) PROPOSED USE	(10) STATIC WATER LEVEL
☐ Domestic ☐ Community ☐ Industrial ☐ Irrigation	ft. below land surface. Date 4-27-06
☐ Thermal ☐ Injection ☐ Livestock ☐ Other	ft. below land surface. Date
(5) BORE HOLE CONSTRUCTION Special Construction: Yes No	Artesian pressurelb. per square inch Date
Depth of Completed Wellft.	(11) WATER BEARING ZONES
Explosives used: Yes No Type Amount	Depth at which water was first found
BORE HOLE SEAL	From To, Estimated Flow Rate SWL
Diameter From To Material From To Sacks or Pounds	48' 75' 200+ GPM 10'
18" 0', 25' Bentonik & 25' 27 Socks	
8, 72, 180	
How was seal placed: Method A B C D E	
Xother Bonkovite Placed @ 1 Sock pr 5 min Kate	(12) WELL LOG Ground Elevation
Backfill placed from ft. to ft. Material	Material From To SWL
Gravel placed from ft. to ft. Size of gravel	Lopsoil 0 1
(C) CIA CINIC/I INICID	Brown Sand Alband 19 50
(6) CASING/LINER Diameter From To Gauge Steel Plastic Welded Threaded	Black Gravel & Sand 50 75
	Blue Clay 75 103
	Blue Clay was 103 120
Liner: None.	Blue Oldy 120 138 Brown Clay 138 153
Liner: None	Blue Clay 153 180
Drive Shoe used 🔲 Inside 🔲 Outside 🛣 None	
Final location of shoe(s)	No Water Found In Clays
(T) PERFOR LEVOLG GOVERNO	Below 1141
(7) PERFORATIONS/SCREENS Perforations Method Air Per Stator	
Screens Type Material	11-20-11
- "	Date Started 4-25-06 Completed 4-27-06
From To Slot Number Diameter Tele/pipe Casing Liner	(unbonded) Water Well Constructor Certification
11 1 mm - 1 E M M 11 1 1 1 1 1 1	I certify that the work I performed on the construction, deepening, alteration, or abandonment of this well is in compliance with Oregon water supply well
48' 75' Z'X2" 160	construction standards. Materials used and information reported above are true to
	the best of my knowledge and belief.
	WWC Number Date
(O) NUDLE PROPER AND A COLUMN A	WWC Nulliber Date
(8) WELL TESTS: Minimum testing time is 1 hour ☐ Pump ☐ Bailer	Signed
Yield gal/min Drawdown Drill stem at Time	(bonded) Water Well Constructor Certification
200+ 68m 114 1 HE	I accept responsibility for the construction, deepening, alteration, or
	abandonment work performed on this well during the construction dates reported
	above. All work performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge
Temperature of water Depth Artesian Flow Found	and belief.
Was a water analysis done? ☐ Yes By whom	WWW. 1 751 5 W-28-51
Did any strata contain water not suitable for interded in the land of the land	WWC Number 751 Date 4-28-06
Salty Muddy Odor Colored Other	Signed Donald Ilovins
Depth of strata:	Signed Donald I foring Time.