## **LINN 57626**

## STATE OF OREGON

VATER SUPPLY WELL REPORT	WELL I.D. # L	<u>873</u>
as required by ORS 537.765)	CTAPT CAPP #	1900

Instructions for completing this report are on the last page of this form.		
(1) LAND OWNER Well Number DR-2090 (9) LOCATION OF WELL (legal description)  County LINN		
Address 26366 GAP ROAD	Tax Lot Lot	
City BROWNS VILLE State OREGON Zip 97327	Township 14 Po Range 3 5 or WWM	
(2) TYPE OF WORK New Well	Section 12 NE 1/4 NE 1/4	
Deepening Alteration (repair/recondition) Abandonment Conversion	Lat	
Deepening Atteration (repair/recondition) Abandonment Conversion	Lat '" or (degrees or decimal)  Long o '" or (degrees or decimal)	
(3) DRILL METHOD  Rotary Air ☐ Rotary Mud ☐ Cable ☐ Auger ☐ Cable Mud ☐ Other	Street Address of Well (or nearest address) 26715 Gap Ro. BROWNSUING DREGON	
(4) PROPOSED USE  ☐ Community ☐ Industrial ☐ Irrigation	(10) STATIC WATER LEVELft. below land surface. Date	
☐ Thermal ☐ Injection ☐ Livestock ☐ Other	ft. below land surface. Date	
(5) BORE HOLE CONSTRUCTION Special Construction: Yes No	Artesian pressure lb. per square inch Date	
Depth of Completed Well 1 ft.  Explosives used: Yes No Type Amount Depth at which water was first found 75		
BORE HOLE SEAL	From To Estimated Flow Rate SWL	
Diameter From To Material From To Sacks or Pounds 12" O 25 Rentound O 25 14 Sacks	75 90 100+ GPM 14	
	75 10 700 9 11	
8' 25 91		
	l	
How was seal glaced: Method A B C D E	(12) WELL LOG Ground Elevation	
Backfill placed fromft. Material	Material From To SWL	
	1 Too Soil . 0 1	
Gravel placed fromft. Size of gravel	CLAY-BROWN W GRAVEL 1 5	
(6) CASING/LINER	CLAY- GRAY N GRAVEL 5 20	
Diameter From To Gauge Steel Plastic Welded Threaded	CLAY-6RAY 20 68 SANO-BLACK 68 73	
Casing: 8" +1 92 1350 \	SANO-BLACK 68 73 GRAVEL WISAND -BLACK 73 92 14'	
<del></del>	CLAY - TAN 92 93	
Liner:		
Liner:		
Drive Shoe used ☐ Inside ☑ Outside ☐ None		
Final location of shoe(s) 92'		
AND DEDECT A MICHIGAGE CONTENTS		
(7) PERFORATIONS/SCREENS Perforations Method HOLTE	l—————————————————————————————————————	
Screens Type SLOT Material STEEL	10 10 01	
<del>-</del>	Date Started 12-19-06 Completed 12-30-06	
From To Slot Number Diameter Tele/pipe Casing Liner (unbonded) Water Well Constructor Certification		
75 90   Size   600   8"   size   \$ \B	I certify that the work I performed on the construction, deepening, alteration, or	
75 90 741 600 8	abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to	
	the best of my knowledge and belief.	
<del></del>		
	WWC Number 1667 Date 12-31-06	
(8) WELL TESTS: Minimum testing time is 1 hour  Pump Bailer Air Flowing Artesian  Signed Signed		
Yield gal/min Drawdown Drill stem at Time	(bonded) Water Well Constructor Certification	
100+ 85' 1 Hour	I accept responsibility for the construction, deepening, alteration, or	
	abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water	
<u> </u>	supply well construction standards. This report is true to the best of my knowledge	
Temperature of water Depth Artesian Flow Found	and belief.	
Was a water analysis done? Yes By whom	WWC Number 1064 Date: 12-31-06	
Did any strata contain water not suitable for intended use?	WWC Number Date 12-31-86	
Salty Muddy Odor Colored Other NECEIVED	Signed dans U. luga	
Depth of strata:		