STATE OF OREGON
WATER SUPPLY WELL REPORT
(as required by OPS 537 765 & OAR 690-205-0210)

LINN 60324

WELL I.D. LABEL# L 97994

START CARD # 1017648

ORIGINAL LOG #

(as required by ORS 537.765 & OAR 690-205-0210)	11/5/2012	ORIGINAL LOG #	#	
(1) LAND OWNER Owner Well LD				
First Name Last Name	- (9) LOCA	TION OF WELL (legal	description)	
Company OREGON STATE UNIVERSITY		County LINN Twp 11.00 S N/S Range 5.00 W E/W WM		
Address 128 STRAND HALL	- Sec 36	Sec 36 SE 1/4 of the NW 1/4 Tax Lot 400		
Address 128 STRAND HALL City CORVALLIS State OR Zip 97331 (2) TYPE OF WORK		Tax Map Number Lot Lat " or 44.57322000 DMS or DD		
(2) TYPE OF WORK New Well Deepening Conversion Alteration (complete 2a & 10) Abandonment(complete 2a & 10)	Dn Lat	°" or _44.573220	00	DMS or DD
(2a) PRE-ALTERATION	Long	° " or -123.2436	0000	DMS or DD
Dia + From To Gauge Stl Plstc Wld Thrd		Street address of well	learest address	
Casing:	11	LECTRIC RD. S, OR. 97333		
Material From To Amt sacks/lbs Seal:	CORVALLI	5, UK. 9/555		
(3) DRILL METHOD	(10) STAT	TIC WATER LEVEL		
Rotary Air Rotary Mud Cable Auger Cable Mud	Eviatina	Wall / Dra Altanation	te SWL(psi) +	SWL(ft)
Reverse Rotary Other	Complet	Well / Pre-Alteration ed Well		
(4) PROPOSED USE Domestic X Irrigation Community		Flowing Artesian?	Dry Hole?	
Industrial/ Commercial Livestock Dewatering	WATER BEA		water was first found	
Thermal Injection Other	SWL Date	•	Est Flow SWL(psi)	
(5) BORE HOLE CONSTRUCTION Special Standard (Attac				
Depth of Completed Well 43.00 ft.	(th copy) 10/6/2012	21 35	700	21
BORE HOLE SEAL	sacks/			
Dia From To Material From To Amt	lbs			
14 0 20 Cement 0 20 15	S			
10 20 43				
	(11) WELI	(11) WELL LOG Ground Elevation 217.00		
How was seal placed: Method A B XC D E		Material	From	То
Other	HARD TOP		0	6
Backfill placed from ft. to ft. Material	DARK BRO		6 10	10
Filter pack from ft. to ft. Material Size		LTY SAND & GRAVEL	12	19
Explosives used: Yes Type Amount		ND & GRAVEL	19	23
(5a) ABANDONMENT USING UNHYDRATED BENTONITE		D & GRAVEL	23	29
Proposed Amount Actual Amount	GRAY & BETAN CLAY	ROWN, SAND & GRAVEL	29 35	35
(6) CASING/LINER	DITTECTA		36	36
Casing Liner Dia + From To Gauge Stl Plstc Wld 10 X 5 43 .250 © X	Thrd			
● ○ 10 × 5 43 .250 ● ○ ×	H II			
Shoe Inside Outside Other Location of shoe(s) 43				
Temp casing \boxed{X} Yes Dia 14 From 0 To 20				
(7) PERFORATIONS/SCREENS				
Perforations Method MILLS KNIFE Screens Type Material	Data Stants	A0/0/2012 Cor	mplete 10/12/2012	2
	Tele/ Date Starte			
		Water Well Constructor Cert		
Perf Casing 10 27 35 .375 2.25 250		the work I performed on the t of this well is in complian		
		standards. Materials used and		
		y knowledge and belief.		
	License Nun	nber	Date	
(8) WELL TESTS: Minimum testing time is 1 hour	Signed			
Pump Bailer Air Flowing Artesi	an			
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	¬ l` ′	ater Well Constructor Certific		
475 4 32 2		onsibility for the construction,		
	work perform	ned on this well during the const uring this time is in complian	ruction dates reported nce with Oregon w	u above. All work ater supply wel
Temperature 55 °F Lab analysis Yes By		standards. This report is true to		
· — — — — ·	License Nun	nber 1629	Date 11/5/2012	
Water quality concerns? Yes (describe below) TDS amount Description Amount Un	its			
	Contact Info	(optional)		