STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210) (1) | # |

WELL I.D. LABEL# L		
START CARD#	1041530	
ORIGINAL LOG#		

(1) LAND OWNER Owner Well I.D. 5966		<u> </u>	
First Name Last Name Company Mayfield Farm, LLC	(9) LOCATION OF WELL (legal description)		
Address 18555 SW Teton Ave	County LINN Twp 10 S N/S Range 3		
City Tualatin State OR Zip 97062	Sec 18 NE 1/4 of the SW 1/4 Tax Lo	t 401	
(2) TYPE OF WORK   X New Well   Deepening   Conversion	Tax Map Number Lot Lat " or "		
Alteration (complete 2a & 10) Abandonment (complete 5a)		DMS or DD	
(2a) PRE-ALTERATION	Long o ' or Nearest address	DMS or DD	
Casing:			
Material From To Amt sacks/lbs	38831 Groshong Rd. NE - Albany, OR 97321		
Seal:			
(3) DRILL METHOD	(10) STATIC WATER LEVEL Date SWL(psi)	+ SWL(ft)	
Rotary Air Rotary Mud Cable Auger Cable Mud	Existing Well / Pre-Alteration		
Reverse Rotary Other	Completed Well 12-14-2018 18		
(4) PROPOSED USE	Flowing Artesian? Dry Hole?		
Industrial/Commercial Livestock Dewatering	WATER BEARING ZONES Depth water was first for		
ThermalInjectionOther	SWL Date From To Est Flow SWL(p	osi) + SWL(ft)	
(5) BORE HOLE CONSTRUCTION Special Standard (Attach copy)	12-14-2018 20 50 200	18	
Depth of Completed Well 58 ft.			
BORE HOLE SEAL sacks/ Dia From To Material From To Amt 1bs			
Dia         From         To         Material         From         To         Amt         lbs           16         0         58         Bentonite         0         18         14         S			
Calculated 14	<u> </u>		
Calculated	(11) WELL LOG Ground Elevation		
How was seal placed: Method A B C D E	Glouid Lacyanon	То	
X Other Poured dry	Material From Brown clay 0		
Backfill placed from ft. to ft. Material	Cemented sand and gravel 20		
Filter pack from 18 ft. to 25 ft. Material round rock Size 3/4-1/2	Sand & gravel 25		
Explosives used: Yes Type Amount	Gray clay 50 Blue clay 55		
(5a) ABANDONMENT USING UNHYDRATED BENTONITE	Side oray		
Proposed Amount Pounds Actual Amount Pounds			
(6) CASING/LINER	Allowed to naturally cave between 16" & 12" and		
Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	then added gravel pack up to 18'		
● ○ 12 × 2 60 250 ● ○ × □			
R-H-H-H-H-H-H	JONES DRILLING CO., INC. 9		
	11	्रिस् स	
		1. 2	
Shoe Inside Outside Other Location of shoe(s)	LEBANON, OR 97355		
Temp casing Yes Dia From To	541-367-2560 541-451-2686		
(7) PERFORATIONS/SCREENS	1-800-915-8388		
Perforations Method Torch cut			
Screens Type Material Perf/S Casing/ Screen Scrn/slot Slot # of Tele/	Date Started 12-11-2018 Completed 12-28	-2018	
creen Liner Dia From To width length slots pipe size	(unbonded) Water Well Constructor Certification		
Perf         Casing         12         18         58         3/8         10         480	I certify that the work I performed on the construction, de		
	abandonment of this well is in compliance with Orego construction standards. Materials used and information repo		
	the best of my knowledge and belief.		
	License Number 1888 Date 01-22-20	119	
(8) WELL TESTS: Minimum testing time is 1 hour	Simul		
Pump	Signed Julium		
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	(bonded) Water Well Constructor Certification		
200 26 48 4	I accept responsibility for the construction, deepening, alter		
<del></del>	work performed on this well during the construction dates rep performed during this time is in compliance with Orego		
Temperature 55 °F Lab analysis Yes By	construction standards. This report is true to the best of my k		
Temperature 55 °F Lab analysis Yes By Water quality concerns? Yes (describe below) TDS amount 200	License Number 1684 / / Date 01-22-2019		
From To Description Amount Units		<del></del>	
	Signed C	<del></del>	
	Contact Info (on floral)	<del></del>	