STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210) LINN 62635

3/22/2019

WELL I.D. LABEL# L 132235 START CARD # 1042190 ORIGINAL LOG #

		1 age	1 01	_
L	132235			
	1042190			

(1) LAND OWNER Owner Well I.D. DR-3381 First Name STAN AND LORI Last Name BOSHART			
Company	(9) LOCATION OF WELL (legal description)		
Address 34877 KNOX BUTTE RD. E	County LINN Twp 11.00 S N/S Range 4.		
City ALBANY State OR Zip 97322	Sec 26 SE 1/4 of the NE 1/4 Tax Lo	t <u>700</u>	
(2) TYPE OF WORK New Well Deepening Conversion	Tax Map Number Lot Lat ' ' or _44.58631900		
Alteration (complete 2a & 10) Abandonment(complete 5a)	Lat or 44.58631900	DMS or DD	
(2a) PRE-ALTERATION	Lat or _44.58031900 Long or123.13427600 Output address of well Nearest address	DMS or DD	
Dia + From To Gauge Stl Plstc Wld Thrd	Street address of well • Nearest address		
Casing:	ACROSS STREET FROM:		
Material From To Amt sacks/lbs	31415 ALLEN LANE		
Seal:	(10) OTA THO WATER I DIVEL		
(3) DRILL METHOD	(10) STATIC WATER LEVEL Date SWL(psi)	L CTTT (C)	
Rotary Air Rotary Mud Cable Auger Cable Mud	Existing Well / Pre-Alteration Date SWL(psi)	+ SWL(ft)	
Reverse Rotary Other	Completed Well 3/21/2019	15	
(4) PROPOSED USE Domestic X Irrigation Community	Flowing Artesian? Dry Hole?		
Industrial/ Commercial Livestock Dewatering			
	WATER BEARING ZONES Depth water was first for		
Thermal Injection Other	SWL Date From To Est Flow SWL(p	osi) + SWL(ft)	
(5) BORE HOLE CONSTRUCTION Special Standard (Attach copy	3/21/2019 51 110 200	15	
Depth of Completed Well 159.00 ft.			
BORE HOLE SEAL sacks/			
Dia From To Material From To Amt lbs	,		
12 0 34 Bentonite 0 34 20 S			
8 34 159 Calculated 19.28	1		
Calculated	(11) WELL LOG Ground Flavation		
	Oround Elevation		
How was seal placed: Method A B C D E	Material From		
X Other POURED DRY	Topsoil 0 Clay Brown Sticky 1		
Backfill placed from ft. to ft. Material	Clay Brown Sticky 1 Clay Brown 7		
Filter pack from ft. to ft. Material Size	Clay Brown/Gray 15		
Explosives used: Yes Type Amount	Clay Brown/Gray Soft w/ Some Gravels 21		
(5a) ABANDONMENT USING UNHYDRATED BENTONITE	Gravels Brown w/ Some Clay 28		
Proposed Amount Actual Amount	Gravels w/ Course Sand Brown 35		
	Gravels Black w/ Sand Course 51		
(6) CASING/LINER Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	Clay Black Sandy w/ Small Gravels 67	7 70	
2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	Clay Gray 70	74	
● 8 X 1.8 159 .250 ● X □	Gravels Black w/ Sand Course 74	4 83	
	Gravels Small Black w/ Some Clay Layers 83	3 87	
	Clay Gray Packed 87		
	Gravels Large w/ Some Course Sand 89		
Shoe X Inside Outside Other Location of shoe(s) 159	Gravels Black w/ Wood 10		
	Gravels Medium Black/Blue w/ Sand 10 Gravels Large w/ Sand Black 10		
Temp casing Yes Dia From + To	Clay Green 11		
(7) PERFORATIONS/SCREENS	Clay Blue/Gray 11		
Perforations Method Holte Air Perforator			
Screens Type Material	Date Started 3/18/2019 Completed 3/21/2	2019	
Perf/ Casing/ Screen Scrn/slot Slot # of Tele/ Screen Liner Dia From To width length slots pipe size	(unbonded) Water Well Constructor Certification		
Screen LinerDiaFromTowidthlengthslotspipe sizePerfCasing875110.2511260	I certify that the work I performed on the construction, de-	epening, alteration, or	
101 Cusing 0 73 110 120	abandonment of this well is in compliance with Orego		
	construction standards. Materials used and information repo		
	the best of my knowledge and belief.		
	License Number 1974 Date 3/21/201	9	
(8) WELL TESTS: Minimum testing time is 1 hour			
· ·	Signed CJ NUGENT (E-filed)		
	(bonded) Water Well Constructor Certification		
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr) 200 155 2			
200 133 2	I accept responsibility for the construction, deepening, alter		
	work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well		
To OF LI 1 V P	construction standards. This report is true to the best of my k		
Temperature 53 °F Lab analysis Yes By	•	<u> </u>	
Water quality concerns? Yes (describe below) TDS amount 144 ppm From To Description Amount Units	License Number 664 Date 3/22/2019		
2 South Paris	Signed CHARLES NUGENT (E-filed)		
	Contact Info (optional) Nugent Drilling Co. Lebanon Oregon	<u> </u>	
	TID A DOWN KEN IM		

LINN 62635

WELL I.D. LABEL# L 132 START CARD # 104 ORIGINAL LOG #

		•
L# L	132235	
D #	1042190	
G#		

continuation page	3/22/2019	ORIGINAL LOG#	12170	
(2a) PRE-ALTERATION	Water Quali	ity Concerns		
Dia + From To Gauge Stl Plstc Wld Thrd	From T		Amount	Units
Material From To Amt sacks/lbs				
(5) BORE HOLE CONSTRUCTION	— (10) STATIO	C WATER LEVEL		
DODE HOLE CEAL	SWL Date	From To Est Flow	SWL(psi) +	SWL(ft)
Dia From To Material From To Amt	acks/			
Calculated				
Calculated			<u> </u>	
Calculated				
Calculated	_			
Calculated			\vdash	+
FILTER PACK	(14) 11/15/1	T 0.0		
From To Material Size	(11) WELL			
		Material	From	To
	Clay Brown Sa	Some Small Gravels Black	121 124	124 132
	Clay Gray w/ S	Small Brown Layers	132	138
(6) CASING/LINER	Sand Black Pad Clay Gray w/ S		138 141	141 150
Casing Liner Dia + From To Gauge Stl Plstc Wld Th	Clay Green w/		150	159
	¬			
	-		+	
	_		+	
]			
	_			
			+	
7) PERFORATIONS/SCREENS				
2	Γele/		-	
Screen Liner Dia From To width length slots pi	pe size			
			+	
			+	
	Comments/	Remarks		
(8) WELL TESTS: Minimum testing time is 1 hour	w ater Measure	ement was Approx GPM.		
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)				
	I			