## STATE OF OREGON 2020 LINN 62889 WELL I.D. LABEL# L 134778 START CARD # 1044664 WATER SUPPLY WELL REPORT evised (as required by ORS 537.765 & OAR 690-205-0210) **ORIGINAL LOG#** (1) LAND OWNER Owner Well I D. 6053 First Name Amy Last Name Doerfler (9) LOCATION OF WELL (legal description) Company K2A Properties LLC \_\_\_\_ Twp\_10 S N/S Range\_2 Address 12333 Silver Falls Hwy. SE \_\_\_ 1/4 of the NW 1/4 Tax Lot 300 <u>NW</u> City Aumsville State OR Tax Map Number New Well Despening Conversion (2) TYPE OF WORK DMS or DD Lat Alteration (complete 2a & 10) | Abandonment(complete 5a) a or DMS or DD (2a) PRE-ALTERATION Street address of well Stl Piste Wid Thrd Casing: 38331 Densmore Dr. - Jefferson, OR 97352 Material Seal: (10) STATIC WATER LEVEL (3) DRILL METHOD SWL(psi) SWL(R) Rotary Air Rotary Mud Cable Auger Cable Mud Existing Well / Pre-Alteration \_\_Reverse Rotary \_\_\_Other 09-05-2019 Completed Well Domestic X Irrigation Flowing Artesian? Dry Hole? (4) PROPOSED USE Industrial Commercial Livestock Dewatering Depth water was first found 18 WATER BEARING ZONES Thermal Injection Other SWL Date Est Flow SWL(psi) + SWL(A) To (5) BORE HOLE CONSTRUCTION Special Standard (Attach copy) 09-05-2019 110 2,000 11 Depth of Completed Well 110 **BORE HOLE** SEAL sacks From Material To Amt From Ibs 63 18 24 16 0 Bentonite IS 12 63 Calculated 5.5 Cenon 11 15 (11) WELL LOG Calculated 5.5 Grand Elevation B XC How was seal placed. Method . A From To X Other Poured dry Topsoil 0 2 Cobbles & clay 2 5 Backfill placed from . ft. Material ft. to \_ 18 Brown clay 5 Filter pack from ft. Material Size fL to Gravel & sand 18 25 Explosives used: Yes Type\_ Amount Gravel cemented 25 30 30 40 (5a) ABANDONMENT USING UNHYDRATED BENTONITE Gravel & sand RECEIVED Cemented gravel 40 52 **Pounds** Pounds Proposed Amount Actual Amount 52 Red clay 56 (6) CASING/LINER Casing Liner 56 60 Gravel cemented From To Gauge Clay w/some gravel 60 65 X 63 250 Cemented gravel 65 95 OWRD 95 105 Red clay & gravel 105 Cemented gravel 110 Pulled temporary casing back to 18' and deleboral well allowing formation from 18' to 13' to paturally cave Inside Outside Other Location of shoe(s) Jones Drilling Co., Inc. 29400 Santiam Hwy Temp casing X Yes D1a 16 From 0 To 63 Lebanon, OR 97355 (7) PERFORATIONS/SCREENS 1-800-915-8388 on the outside of ia" Perforations Method Torchcut Screens Type Date Started 08-26-2019 Completed <u>09-05-2019</u> Material Perf/S Casing/ Screen # of Tele/ Scm/slot Slot (unbonded) Water Well Constructor Certification

Liner Dia slots Dipe size lengt Perf Casing 12 63 375 12 600 I certify that the work I performed on the construction, deepening, alteration, or abandonment of this well is in compliance with Oregon water supply well

(8) WELL TESTS: Minimum testing time is 1 hour

LLL I LOID. William testing time is I nour							
• Ритр		Oı	Bailer	O Air	r (	Flowing Artesian	
-	Yield gal/m	in_D	awdown_	Drill stem	Pump dept	Duration (	וב)
	1,050		7		30	4	
-		+		+		1	-
L		1				1	
Temperature 61 °F Lub analysis Yes By							
Wa	ter quality co	ncerns?	□Yes	(describe b	elow) TDS	mount 170	
	From	To		_ Descript	tion	Amount	Units

License Number Date 09-26-2019

the best of my knowledge and belief.

(bonded) Water Well Constructor Certification

License Number

Signed

Signed Contact Info (optional) jonesdraling@hotmail.com

construction standards. Materials used and information reported above are true to

I accept responsibility for the construction, deepening, alteration, or abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief

09-26-2019