NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED SEP 1 1967 STATE ENGINEER SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

LINN 6300

State Well No. 11/2w-5

State Permit No.

(1) OWNER:
Name Wilbert Bilyeu
Address Rt 1, Box 259 Albany Oregon

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded ☒
10" Diam. from 0 ft. to 25 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used
Size of perforations 1/2 in. by 1/4 in.
40 perforations from 19 ft. to 25 ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.
Static level 17 ft. below land surface Date 8-1-67
Artesian pressure lbs. per square inch Date

(9) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 80 gal./min. with 70 ft. drawdown after 1 hrs.
Artesian flow g.p.m. Date
Temperature of water 52 Was a chemical analysis made? ☐ Yes ☒ No

(10) CONSTRUCTION:
Well seal—Material used Bentonite.
Depth of seal 18 ft.
Diameter of well bore to bottom of seal 14 in.
Were any loose strata cemented off? ☐ Yes ☒ No Depth
Was a drive shoe used? ☒ Yes ☐ No
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(11) LOCATION OF WELL:
County Linn Driller's well number
¼ ¼ Section 5 T. 11 S R. 2 W W.M.
Bearing and distance from section or subdivision corner
S.E. ¼ Sec 5, T 11, R 2W + part of J W Powell D.L.C. # 40

(12) WELL LOG: Diameter of well below casing 10"
Depth drilled 25 ft. Depth of completed well 25 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
River bottom soil	0	8	
Cemented sand	8	12	
Cemented sand + gravel	12	18	
gravel	18	25	

Work started 7-31 1967 Completed 8-1 1967
Date well drilling machine moved off of well 8-1 1967

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Carl H Saunders (Drilling Machine Operator) Date 8-1, 1967
Drilling Machine Operator's License No. 31

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
NAME Will Amette Irrigation & Equip Co (Person, firm or corporation) (Type or print)
Address Star Route #2 Box 5, Lebanon
[Signed] Carl H Saunders (Water Well Contractor)
Contractor's License No. 49 Date 8-1, 1967

(USE ADDITIONAL SHEETS IF NECESSARY)