	LINN		
NOTICE TO WATER WELL CHUTRACTOR The original and first doby of this report are to be APR 2 2 1966 WATER WE	LL REPORT 6 3530	ש מו	-5P
STATE ENGINEER, SALEM, GREGON FRIGENGINEERTATE OF Within 30 days from the date of well completion. SALEM OREGON (Please types)	F OREGON pe or print) State Well No		
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level		
Name George Dwyer	Was a pump test made? Y Yes \(\sum \) No If yes, by whom? \(\text{OWNER} \)		
Address Rt. 1, Box 301, Albany, Ore.	Yield: 120 gal./min. with 34 ft. drawdown after 3 hrs.		
	" " "		
(2) LOCATION OF WELL:	Bailer test gal./min. with ft. drawdown after hrs.		
County Linn Driller's well number	Artesian flow g.p.m. Date		
½ ½ Section 5 T. 11S R. 2W W.M.	Temperature of water Was a chemical analysis made? Yes No		
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below casing		
	Depth drilled 126 ft. Depth of completed well	106) ft.
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.		
	MATERIAL	FROM	то
(3) TYPE OF WORK (check):	Top Soil	0.1	51
Well ⚠ Deepening ☐ Reconditioning ☐ Abandon ☐	Cemented gravel	51	281
If sandonment, describe material and procedure in Item 12.	Sand and gravel	281	321
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Sand and clay (brown)	321	351
Domestic T Industrial Municipal Rotary Driven	Sand and gravel (brown)	351	48!
Irrigation ₩ Test Well □ Other □ Dug □ Bored □	Sand and gravel (blue)	481	521
(O) CACING INCOMENTATION	Sand and gravel (black) Limestone	52' 105'	105
(6) CASING INSTALLED: Threaded	Mud seam (B/ux)	118	122
8" Diam. from	Limestone	122	126'
Diam. from ft. to ft. Gage ft. Gage			
(F) DEDECORATIONS			
			-
Type of perforator used Size of perforations in. by in.			
perforations from ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			-
perforations from ft. to ft.			<u> </u>
perforations from ft. to ft.			
(8) SCREENS: Well screen installed? ☐ Yes ▼ No			-
Manufacturer's Name			
Model No.			
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	Work started 4-11 19 66 Completed 4-1		<u> 19 6</u> 6
	Date well drilling machine moved off of well 4-19	<u>}</u>	19 66
(9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in sealBentonite	Manufacturer's Name		
Depth of seal	Type: H.P.		
Diameter of well bore to bottom of seal 12 in. Were any loose strata cemented off? Yes Yo Depth	Water Well Contractor's Certification:		
Was a drive shoe used? Yes ☐ No Depth	This well was drilled under my jurisdiction	and this	report is
Was well gravel packed? Yes No Size of gravel;	true to the best of my knowledge and belief.	01110	LCPOLU ID
Gravel placed fromft. toft.	NAME Pyle and Salisbury		
Did any strata contain unusable water? 🔲 Yes 🎽 No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address 1875 9th. St. Lebanon, Ore.		
Method of sealing strata off	— Drilling Machine, Operator's License No		
(10) WATER LEVELS:	[Signed] Ward & Syle	-	
Static level 6 ft. below land surface Date 4-19-66	(Water Well Contractor)	a 1	, i
Artesian pressure lbs. per square inch Date	Contractor's License No. 216 Date H-	20	1966