The original and first property of this report are the AUGA - 1972 WATER WELL REPORT filed with the STATE ENGINEER, SALEM-OREGON DESCRIPTION OF THE Please type or print)

State	Well	No.	115/2W-9	?
-: -				

filed with the MUUTE TOTATE OF OREGON

STATE ENGINEER, SALEMOREGON TOTAL (Please type or print)

within 30 days from the date EM. OR 100 No not write above this line)

State	well M	o /	13/1/1	<i>y</i>
State	Permit	No.	=	-

of west companies.				
(1) OWNER:	(10) LOCATION OF WELL:	-		
Name MRS MABLE BOWMAN	County Linn Driller's well nu	ımber	58	<u> </u>
Address Poute 1 Box 299 Tennessee ROAD	1/4 1/4 Section 9 T.	R. 2W		W.M.
Albany Oregon	Bearing and distance from section or subdivision	on corner	27	O leet.
(2) TYPE OF'WORK (check):	South 294 feet east &		-	Eth
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	east Corner			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found			ft.
Rotary Driven Domestic Industrial Municipal	Static level 9 ft. below land s	urface. D	ate 6/	24/72
Cable	Artesian pressure Ibs. per squar	·		-17-1-
i) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well h			-
64 " Diam. from + 10 Mu ft. to 55 ft. Gage . 250				
"Diam. fromft. toft. Gage	Depth drilled 59 ft. Depth of compl		55	ft.
ft. toft. Gage	Formation: Describe color, texture, grain size a and show thickness and nature of each strature.			
	with at least one entry for each change of format	tion. Repor	t each c	hange in
Perforated? Yes 🗆 No.	position of Static Water Level and indicate prin	cipal water	r-bearin	g strata.
Type of perforator used Acetylene Cutting Torch	MATERIAL	From	То	swl -
Size of perforations 3/2 in. by /O in.	BROWN Top Soil	0	2	145
14 perforations from 43 ft. to 53 ft.	BROWN SANDY CLAY	2	17	15
perforations from	COARSE SAND + Fine GRAVE!	17 8	28	20
perforations from ft. to ft.	SOFT BROWN CLAY	28	47	30
	MEDIUM GRAVEL AND SAND	47 3	55	9
(7) SCREENS: Well screen installed? Yes No				
Manufacturer's Name]	
Type Model No				
Diam, Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.	77 ±	<u> </u>		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? ☐ Yes K No If yes, by whom?				
Yield: gal./min. with ft. drawdown after hrs.	_			
" " "				
	Vergen e			,
" " " "				
Bailer test 30 gal./min. with /2 ft. drawdown after / hrs.		$\perp \perp \perp$		
Artesian flow g.p.m.			i	
mperature of water Depth artesian flow encountered ft.	Work started 6/10/ 1972 Complete	ed la la	24/	1972
(9) CONSTRUCTION:	Date well drilling machine moved off of well	6/24	/	1972
Well seal-Material used BenTonite	Drilling Machine Operator's Certification:			
Well sealed from land surface to 18 ft.	This well was constructed under my Materials used and information reported	direct	super	vision.
Diameter of well bore to bottom of sealin.	best knowledge and belief.	anove a	e mae	to my
Diameter of well bore below seal	[Signed] Lacate Way	Date	8/3/	1972
Number of sacks of cement used in well seal	(Drilling Machine Operator)			• ,
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.	264	*****	
Brand name of bentonite Central Oregan Bentonite Co	Water Wall Contractor's Confisiontion			
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	1_41 · ·	1 41-2	
of water lbs./100 gals.	This well was drilled under my jurisd true to the best of my knowledge and bel		ı tnıs r	eport is
Was a drive shoe used? Z Yes 🔲 No Plugs Size: location ft.	Name FRANK WASY - Well &	DRILL	iva	-
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Typ	e er pri	nt)
Type of water? depth of strata	Address 3435 Pine LANE	HIBA	NY L	IRego.
Method of sealing strata off	[Signed] want we	-94/	*****	
Was well gravel packed? Yes No Size of gravel:	(Water Well Cont	/ ~		
Gravel placed from ft. to ft.	Contractor's License No. 43.3 Date	8/3	<i>5./</i>	, 19. <i>Z.Z</i>