NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion.

RECEIVED APR 10 1964 STATE ENGINEER SALEM, OREGON

LINN 6603

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

State Well No. 11/2W-11

State Permit No.

(1) OWNER:
Name Lee Bender
Address Rt. 2, Box 249, Albany, Oregon

(2) LOCATION OF WELL:
County Linn Driller's well number
¼ ¼ Section 11 T. 11S R. 2W W.M.
Bearing and distance from section or subdivision corner

(3) TYPE OF WORK (check):
New Well [X] Deepening [] Reconditioning [] Abandon []
If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):
Domestic [X] Industrial [] Municipal []
Irrigation [X] Test Well [] Other []

(5) TYPE OF WELL:
Rotary [] Driven []
Cable [X] Jetted []
Dug [] Bored []

(6) CASING INSTALLED:
Threaded [] Welded [X]
10" Diam. from 0 ft. to 36 ft. Gage 28.04
..." Diam. from ... ft. to ... ft. Gage ...
..." Diam. from ... ft. to ... ft. Gage ...

(7) PERFORATIONS:
Perforated? [X] Yes [] No
Type of perforator used Acetylene Torch
Size of perforations ½ in. by 12 in.
33 perforations from 25 ft. to 36 ft.
... perforations from ... ft. to ... ft.
... perforations from ... ft. to ... ft.
... perforations from ... ft. to ... ft.
... perforations from ... ft. to ... ft.

(8) SCREENS:
Well screen installed? [] Yes [X] No
Manufacturer's Name ...
Type ... Model No. ...
Diam. ... Slot size ... Set from ... ft. to ... ft.
Diam. ... Slot size ... Set from ... ft. to ... ft.

(9) CONSTRUCTION:
Well seal—Material used in seal Bentonite
Depth of seal 18 ft. Was a packer used? ...
Diameter of well bore to bottom of seal 14 in.
Were any loose strata cemented off? [] Yes [X] No Depth ...
Was a drive shoe used? [X] Yes [] No
Was well gravel packed? [] Yes [X] No Size of gravel: ...
Gravel placed from ... ft. to ... ft.
Did any strata contain unusable water? [] Yes [] No
Type of water? Depth of strata
Method of sealing strata off

(10) WATER LEVELS:
Static level 8 ft. below land surface Date 3-19-64
Artesian pressure lbs. per square inch Date

(11) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? [X] Yes [] No If yes, by whom? Self
Yield: 125 gal./min. with 19 ft. drawdown after 2 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? [] Yes [X] No

(12) WELL LOG:
Diameter of well below casing 10"
Depth drilled 39 ft. Depth of completed well 39 ft.
Formation: *Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.*

MATERIAL	FROM	TO
Sandy Loam	0	9
Sand & Gravel	9	26
Coarse Gravel	26	38
Blue Clay	38	39

Work started 3-16 1964 Completed 3-19 1964
Date well drilling machine moved off of well 3-20 1964

(13) PUMP:
Manufacturer's Name ...
Type: ... H.P. ...

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Merle Warren Well Drilling
(Person, firm or corporation) (Type or print)
Address Rt. 1, Box 85, Tangent, Oregon

Drilling Machine Operator's License No. 313

[Signed] Merle Warren
(Water Well Contractor)

Contractor's License No. 182 Date 3/27, 1964

(USE ADDITIONAL SHEETS IF NECESSARY)