NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the	WATER WELL REPORT STATE OF OREGON AUG6 1974 State Well No. 115 2W - 18
STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.	(Please type or print) STATE ENGINEER Permit No
(1) OWNED.	(10) LOCATION OF WELL:

(1) OWNER:	(10) LOCATION OF WELL:	2
Name Earl Stutzman	County Linn Driller's well nu	mber
Address Rt. 1, Box 334A, Albany, Ore. 97321	34 34 Section 18 T. 11S	R. 2W W.M.
	Bearing and distance from section or subdivision	n corner
(2) TYPE OF WORK (check):		
New Well 🕻 Deepening 🗌 Reconditioning 🔲 Abandon 🗎	The same of the sa	and the commence of the same
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	1	3 to 62 ft.
Rotary Driven Domestic Industrial Municipal	Static level 810611 ft. below land st	urface. Date 7_11_74
Cable Detted Detted Detter Domestic District Detter	*	
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square	mcn. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well b	elow casing].Q.!!
"Diam. from +09" ft. to 272'07/2" Gage 250Wall	Depth drilled 272 ft. Depth of comple	
ft. Gage	Formation: Describe color, texture, grain size a	
" Diam. fromft. toft. Gage	and show thickness and nature of each stratum	n and aquifer penetrated,
	with at least one entry for each change of format position of Static Water Level and indicate princ	ion. Report each change in
PERFORATIONS: Perforated? X Yes No.		
Type of perforator used Acetylene Torch	MATERIAL	From To SWL
Size of perforations ½ in. by 1277 in.	Top Soil	0 21/2
72 perforations from 102 ft, to 92 ft.	Brown Sandy Clay	21/2 9
72 perforations from 258'07½" ft. to 270'07½" ft.	Brown Sandy Clay & Lg Grav.	9 16
perforations fromft. toft.	Dirty Gravel	16 25
/// CCDEENC.	Sandy Tan Clay	25 35
(7) SCREENS: Well screen installed? Yes X No	Brown Packed Sand	35 43
Manufacturer's Name	Light Brown Clay	43 46 46 58
TypeModel No DiamSlot sizeSet fromft. toft.	Dark Blue Clay	58 62
Diam. Slot size Set from ft. to ft.	Black Sand	62 70
Diam. Slot size Set Holl	Blk Sandy Clay & Gravel	70 74
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Black Clay Grey Clay & Gravel	74 100
	Pea Gravel	100 101
Was a pump test made? Yes \(\sigma\) No If yes, by whom? Self	Dk Grey Clay & Gravel	101 115
Yield: 480 gal./min. with XX ft. drawdown after 2 hrs.	Blue Clay & Gravel	115 141
" 110 " "	Brownish Grey Clay & Fn Grav	
" " " " " " " " " " " " " " " " " " "	Dark Grey Clay	145 160
Bailer test gal./min. with ft. drawdown after hrs.	Packed Coarse Black Sand	160 169
Artesian flow g.p.m.	Brown Clay	169 172
pperature of water Depth artesian flow encountered ft.	Work started 6-18 1974 Complete	ed 7-11- 1974
	Date well drilling machine moved off of well	19
(9) CONSTRUCTION:	Dutilian Machine Operator's Contification	•
Well seal-Material used Bentonite	Drilling Machine Operator's Certification: This well was constructed under my	direct supervision.
Well sealed from land surface toft.	Materials used and information reported	above are true to my
Diameter of well bore to bottom of seal 14 in.	best knowledge and belief.	Date 7-15, 19 74
Diameter of well bore below sealin.	[Signed] (Drilling Machine Operator)	Date //
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	436
Number of sacks of bentonite used in well seal sacks		
Brand name of bentonite Oregon Bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisd	iction and this report is
of water lbs./100 gals.	true to the best of my knowledge and be	lei.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Merle Warren Well Dril	(Type or print)
Did any strata contain unusable water? Yes No	(Person, firm or corporation) Address Rt. I, Box 84, Tangent	t, Ore. 97389
Type of water? depth of strata	Address	4
Method of sealing strata off	[Signed]	run
Was well gravel packed? ☐ Yes ▼ No Size of gravel:	(Water Well Cont	7 10 7
Gravel placed from ft. to ft.	Contractor's License No Date	
	HEETS IF NECESSARY)	SP*45656-119

	Dark Grey Clay	172	180
• •	Dark Grey Sandy Clay	180	193
	Packed Black Sand	193	198
	Form Dark Grey Clay	198	215
	Grey Clay	2 15	242
	Sandy Green Clay	242	247
	Sandy Grey Clay	247	258
	Black Sand & Gravel	258	263
	Blue Clay	263	272

V(N)