NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT LINW STATE OF OREGON

(Please type or print)

			•	i		
State	Well	No.	1161	ZW	- 23	bb

(Do not write above this line)

State	Well	No.	1161	ZW	- 23	.b.b

State Permit No. .....

(1) OWNER:	(10) T.O.G.I.TYON, O
Name INTERNATIONAL PAPER CO	(10) LOCATION OF WELL:
Address PD. BOX 579 LONGUIEN, WASH	Double South Driller's well number SS64  NW 14 NW 14 Section 23 T. //S R. 2 W.M.
(2) TYPE OF WORK (check): WELL NO 2	Bearing and distance from section or subdivision corner
	The second secon
New Well Deepening Reconditioning Abandon I If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 8 ft.
Rotary Driven Domestic Industrial Municipal Domestic Industrial Municipal Domestic	
Bored   Irrigation   Test Well Other	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded M	(12) WELL LOG: Diameter of well below casing
"Diam. from ft. to ft. Gage ft	Formation: Describe color, texture, grain size and structure of materials.
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
(6) PERFORATIONS: Perforated?  Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	BROWN AND BLUE CLAY 0 6
perforations from ft. to ft.	SAND AND GRAVELGROUND &
perforations fromft. toft.	SAND AND GRAVE WATERS 24
perforations from ft. to ft.	BLUTE CLAY 24 28
(7) SCREENS: Well screen installed? Yes \( \subseteq \text{No} \)	
Manufacturer's Name OD JOHOSOU Wes I No	
Type STAINLESS STEEL Model No.	A CONTRACTOR AND
Diam. 12 Slot size 150 Set from 14 ft. to 24 ft.	
Diam. Slot size Set from ft. to ft.	RECEIVED.
(8) WELL TESTS: Drawdown is amount water level is	
lowered below static level	APR2 2 1980
Was a pump test made? Yes 🔲 No If yes, by whom?	WATED PERCUE
ld: 296 gal./min. with 7ft. drawdown after 4 hrs.	SALES DEPT
II	DALEM. OREGON
" " " " " " " " " " " " " " " " " " " "	
Bailer test gal./min. with ft. drawdown after hrs.	
esian flow g.p.m.	Then, the state of
Temperature of water Depth artesian flow encountered ft.	11. 11. 60
(9) CONSTRUCTION:	Work started MAR // 19 80 Completed MAR 25 1950  Date well drilling machine moved off of well MAR 28 19 500
4-14-1	
	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bore below sealin.	[Signed] July 19 80
Number of sacks of cement used in well seal 28 sacks  How was cement grout placed? GROUT WAS PUMPED  FROM BOTTOM 128 AX THE	Drilling Machine Operator's License No. 911
16 IN CASING WAS REMOVED	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Yes 🗆 No Plugs Size: location ft.	true to the best of my knowledge and belief.  Name  Name  Name  Name
Did any strata contain unusable water? 🔲 Yes 🗙 No	Name (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 8110 SE SUNDET LANG PORTLAND ORK
Method of sealing strata off	15in a Kabe NT That I was
Was well gravel packed? ☐ Yes No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 10 Date 1922 21 1980
	Date to the second seco