NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

LINNWATER WELL REPOEREIVED

STATE ENGINEER, SALEM, OREGON 97310 6 196 within 30 days from the date of well completion.

STATE OF OREGONOCT # 1 1974
(Please type or print)

State Well No. 115 2W-23

(Do not write above this STATE ENGINEER State Permit No. SALEM. OREGON

App- 6-6646

(1) OWNER:	(10) LOCATION OF WELL:
Name Ammon Bros.	County Linn Driller's well number
Address Rt. 2, Box 258, Albany, Ore. 97321	14 14 Section 23 T. 11S R. 2W W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well ∰ Deepening □ Reconditioning □ Abandon □	1 100 100 110 110 110 110 110 110 110 1
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 20
Rotary Driven Demostic Demostic Description	
Towns of Decree 1	Static level 10 ft. below land surface. Date 10-10-74
Bored Irrigation Test well Other	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
12 "Diam from +08" ft. to 26' MST. Gage 250Wall	Diameter of well below casing
" Diam, from	Depth drilled 26 ft. Depth of completed well 26 ft.
ft. Gageft.	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
(6) DEDEODATIONS.	with at least one entry for each change of formation. Report each change in
(6) PERFORATIONS: Perforated? Xyes \(\text{No.} \)	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Acetylene Torch	MATERIAL From To SWL
Size of perforations ½ in. by 12 in.	Top Soil 0 2
60 perforations from18 ft. to26 ft.	Loam 2 9
perforations from ft. to ft.	Dirty Gravel 9 15
perforations from ft. to ft.	Brown Sand & Lg. Gravel 14 241/2
(7) SCREENS: Well screen installed? ☐ Yes 🖔 No	Sandy Brown Clay 24½ 26
Manufacturer's Name	100
Type Model No.	
Diam. Slot size Set from ft. toft.	
Diam Slot size Set from ft. to ft.	
(0) WILL I DECIDE. Drawdown is amount water land to	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes ☑ No If yes, by whom?	<u> </u>
t: gal./min. with ft. drawdown after hrs.	
" " " " " " " " " " " " " " " " " " " "	
" " " " " " " " " " " " " " " " " " " "	
Bailer test 120 gal./min. withNO ft. drawdown after 1 hrs.	
sian flow g.p.m.	
	70.0
Temperature of water Depth artesian flow encountered ft.	Work started 10-9 19_74completed 10-10 19.74
(9) CONSTRUCTION:	Date well drilling machine moved off of well 10-10 19 74
Well seal-Material used <u>Bentonite</u>	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal16in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below sealin.	[Signed] Date 0 1, 1974
Number of sacks of cement used in well seal sacks	
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 436
Brand name of bentonite Oregon Bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Xes \(\subseteq No \) Plugs Size: location ft.	Name Merle Warren Well Drilling
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address Rt. 1 Box 84, Tangent, Ore. 97389
Method of sealing strata off	[Signed] Melle Warren
Was well gravel packed? 🔲 Yes 🏋 No Size of gravel:	(Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 182 Date / 1974