

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED JUN 23 1967

WATER WELL REPORT

STATE OF OREGON

(Please type or print) (Do not write above this line)

STATE ENGINEER

LINN 6977

State Well No. 11/2w-35

State Permit No.

(1) OWNER:

No. 15 M. OREGON

Name (Vernon Dee Carter) W. H. Long

Address (Rt. 2 Box 234) R. 2 Box 204 Lebanon, Oregon

(2) TYPE OF WORK (check):

New Well [X] Deepening [ ] Reconditioning [ ] Abandon [ ]

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [ ] Driven [ ] Cable [X] Jetted [ ] Dug [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [ ] Industrial [ ] Municipal [ ] Irrigation [X] Test Well [ ] Other [ ]

(5) CASING INSTALLED:

10" Diam. from 0 ft. to 35 ft. Gage STD

(6) PERFORATIONS:

Perforated? [X] Yes [ ] No.

Type of perforator used

Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [ ] Yes [X] No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.

Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 14 ft. below land surface Date 5-9-67

Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [X] Yes [ ] No If yes, by whom?

Yield: 475 300 gal./min. with 2 ft. drawdown after 2 hrs.

200 " 1 " " 1 "

75 " None " 1 "

Ballor test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m. Date

Temperature of water Was a chemical analysis made? [ ] Yes [ ] No

(10) CONSTRUCTION: drilled with slurry of

Well seal—Material used Bentonite

Depth of seal 20 ft.

Diameter of well bore to bottom of seal in.

Were any loose strata cemented off? [ ] Yes [X] No Depth

Was a drive shoe used? [ ] Yes [X] No

Did any strata contain unusable water? [ ] Yes [X] No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? [ ] Yes [ ] No Size of gravel:

Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Linn Driller's well number 1/4 1/4 Section 35 T. 11s R. 2W W.M.

Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 10"

Depth drilled 35 ft. Depth of completed well 35 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include: sandy loam (0-4), course sand and fine gravel (4-12), course gravel and sand (12-23), medium gravel, partly cemented (23-35).

Work started 4-27-67 19 Completed 5-9-67 19

Date well drilling machine moved off of well 5-9-67 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Ronald S. Witham Date 6-20-67 (Drilling Machine Operator)

Drilling Machine Operator's License No. 503

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Raymond C. Gallatly (Person, firm or corporation) (Type or print)

Address Box 1 Philomath, Oregon

[Signed] Raymond C. Gallatly (Water Well Contractor)

Contractor's License No. 77 Date 6-21-67 19