STATE ENGINEEWATER WELL REPORT 7003

SALEM, CRESCH STATE OF OREGON (3/260

File Original and First Copy with the STATE ENGINEER, SALEM, OREGON SALEM, OREGON STATE OF	the state of the s	1083	
(1) OVNER: Christenson	(11) WELL TESTS: Drawdown is amount lowered below static le	evel	is
Address American Don' 247 E	Was a pump test made? ☐ Yes ☐ No If yes, by who Yield: gal./min. with ft. drawdov		hrs.
Telronon Overen	n n	VII GIBEI	**
(a) I OCATION OF WEIL.	" "		**
(2) LOCATION OF WELL:	Bailer test gal./min. with ft. drawdov	vn after	hrs.
Owner's number, if any— 10 8 3 1/E 45E 4 Section 75 T. /15 R. 2, W.W.M.	Artesian flow g.p.m. Date		
Bearing and distance from section or subdivision corner 1099	Temperature of water Was a chemical analysis m	ade? 🔲 Y	es 🕡 No
South & 25.75 St West from	(12) WELL LOG; Diameter of well	10 4	inches.
NF corner of andrews Rees DLC	Depth drilled 30 ft. Depth of completed v		う ft.
19. TIIS 182 w, W north & golf	Formation: Describe by color, character, size of mater show thickness of aquifers and the kind and nature of		cture, and
E 4 18035 7 115 1 2 w 10	show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each	the materi change of j	al in each formation.
	MATERIAL	FROM	то
(3) TYPE OF WORK (check):	sonder Tomm	121	
New Well □ Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 11.	sive grove	12"	301
PROPOSED USE (check): (5) TYPE OF WELL:			
	Cloy	30	<u>.</u>
Domestic Industrial Numerical Cable Jetted		-	
Irrigation Test Well Other Dug Bored		-	
(6) CASING INSTALLED: Threaded □ Welded □			
10" Diam. from ft. to Calling ft. Gage Clouds			
"Diam. from	•		
(7) PERFORATIONS: Perforated? Yes \(\sigma \) No			
SIZE of perforations in. by in.		 	<u> </u>
15 perforations fromft. toft		-	
perforations from ft. to ft	, · · · · · · · · · · · · · · · · · · ·	 	
perforations fromft. toft			
perforations fromft. toft			
perforations from ft. to ft			
(8) SCREENS: Well screen installed Yes No			
Manufacturer's Name	*.	_	ļ
Type Model No		-	
Dirm. Slot size Set from ft. to ft.	1 / /		<u> </u>
Slot size Set from ft. to ft.	Work started for ort 19 h Completed	some	19
(9) CONSTRUCTION:	(13) PUMP!	4	· / · //
Was well gravel packed?	Manufacturer's Name Mayure was Ce	nlve,	fical
Gravel placed from ft. to ft.	Type: shallwell pump	н.р	15,
Was a surface seal provided? Yes No To what depth? ft			
Material used in seal— Did any strata contain unusable water? ☐ Yes ☐ No	Well Driller's Statement: This well was drilled under my jurisdiction	and this	report is
Type of water? Depth of strata	true to the best of my knowledge and belief,	and mis	report is
Method of sealing strata off	want do at ha	M. C	esel
(10) WATER LEVELS:	NAME (Person, firm or corporation)	Type or pri	nt)
Static level 2 5 ft. below land surface Date	Address co not own fi	Lever	59.7
Artesian pressure lbs. per square inch Date	Driller's Well franker Tenne		
Log Accepted by:	[Signed] (Well Driller)		
[Signed] Date, 19	License No Date		, 19