

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED MAY 11 1972

WATER WELL REPORT

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

STATE ENGINEER SALEM, OREGON

(Please type or print)

(Do not write above this line)

State Well No. 11/3W-4

State Permit No.

(1) OWNER:

Name Walter Underwood
Address 3532 Dunlap Ave., Albany, Ore. 97321

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven []
Cable [X] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal []
Irrigation [] Test Well [] Other []

CASING INSTALLED:

Threaded [] Welded [X]

6" Diam. from +8" ft. to 79 1/2" ft. Gage 17#

PERFORATIONS:

Perforated? [X] Yes [] No.

Type of perforator used Acetylene Torch
Size of perforations 3/8 in. by 12 in.
36 perforations from 70 1/2 ft. to 79 1/2 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [X] No
Yield: gal./min. with ft. drawdown after hrs.
Bailer test 70 gal./min. with 7 1/2 ft. drawdown after 1 1/2 hrs.

(9) CONSTRUCTION:

Well seal—Material used Bentonite
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal 4 sacks
Brand name of bentonite Oregon Bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? [X] Yes [] No Plugs Size: location ft.
Did any strata contain unusable water? [] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Linn Driller's well number
1/4 1/4 Section 4 T. 11S R. 3W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 46 ft.
Static level 12 ft. below land surface. Date 5-3-72
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6"

Depth drilled 80 ft. Depth of completed well 80 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Top Soil, Brown Clay, Brown Clay & Gravel, Dirty Gravel, Blue Clay, Black Sand & Gravel, Black Sandy Clay, Black Clay & Gravel.

Work started 4-28 1972 Completed 5-3 1972
Date well drilling machine moved off of well 5-3 1972

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] [Signature] Date 5/6, 1972
(Drilling Machine Operator)
Drilling Machine Operator's License No. 436

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Merle Warren Well Drilling
Address Rt. 1, Box 84, Tangent, Ore. 97389
[Signed] [Signature]
(Water Well Contractor)
Contractor's License No. 182 Date 5/6, 1972