NOTICE TO WATER WELL CONTROL TO THE Original and first copy of this report are to be filed with the filed with the FEB 29 19/2 STATE OF OREGON STATE ENGINEER, SALEM, OREGON 97940 C ENGINEER type or print) of well completion.

SALEM OF (Do not write above this line)

WELL REPORT LINE

State V			11.	/3	M	-//	cc
State V	Vell 1	Vo.			VV.	£.1	

State Permit No. ..

(1) OWNER:	(10) LOCATION OF WELL:					
Name Morse Brothers	County <b>Linn</b> Driller's well nu	mber	13272	<u>D</u>		
Address P.O. Box 7. Lebanon, Oregon 97355	SW 1/2 SW 1/2 Section 11 T. 11S	R,	3W	W.M.		
	Bearing and distance from section or subdivision	on corne	<u>r</u>	**		
(2) TYPE OF WORK (check):						
New Well		54				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	3	0	ft.		
Rotary Driven Domestic Industrial M Municipal	Static level 4 ft. below land s	urface.	Date 2/	17/72		
Cable       I       Jetted       □         Dug       □       Bored       □       Irrigation       □       Test Well       □       Other       □	Artesian pressure lbs. per squar		`	F- 1 *		
CASING INSTALLED:  8 "Diam. from 0 ft. to 212 ft. Gage 250  "Diam. from ft. to ft. Gage PERFORATIONS:  Perforated? X Yes No.	(12) WELL LOG: Diameter of well below casing					
Type of perforator used Mills Knife	MATERIAL	From	То	swL		
Size of perforations 1/4 in. by 3 in.	Crushed rock	0	3			
	Gravel & sand	3	32	<b>30</b> 8		
140 perforations from 129 ft. to 152 ft.	Brown clay	32	47			
	Grav clav	47	56			
	Gray clay & light sand	54	84			
(7) SCREENS: Well screen installed?  Yes  No	Gray clay	84	96	<u></u>		
Manufacturer's Name	Sand & gravel	96	110			
Type Model No.	Small gravel & sand	110	121			
Diam. Slot size	Gray sand & clay	121	129			
Diam Slot size Set from ft. to ft.	Gravel	129				
(8) WELL TESTS: Drawdown is amount water level is	Gravel & brown sand	154	172			
iowered below static level	Gray clay with black sand	172	205	4		
Was a pump test made?  Yes No If yes, by whom?	Gray clay with sand	203	2.12			
Yield: gal./min. with ft. drawdown after hrs.			<u> </u>			
ıı ıı ıı						
n n n						
Bailer test 70 gal./min. with 12 ft. drawdown after 2 hrs.	15.					
Artesian flow g.p.m.						
erature of water 53 Depth artesian flow encountered ft.	Work started 2/5 19 72 Complete	eđ	2/17	19 72		
(9) CONSTRUCTION:	Date well drilling machine moved off of well		2/17	19 72		
Well seal—Material used Cement  Well sealed from land surface to 40 ft.  Diameter of well bore to bottom of seal 12 in.  Diameter of well bore below seal 8 in.  Number of sacks of cement used in well seal 22 sacks  Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's Certification:  This well was constructed under my Materials used and information reported best knowledge and belief.  [Signed] (Drilling Machine Operator)  Drilling Machine Operator's License No.	direc above Date	2/28	to my		
Brand name of bentonite			•	•		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		• .• •			
of water lbs./100 gals.	This well was drilled under my jurisd true to the best of my knowledge and be	iction a lief.	nd this 1	eport is		
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	Name Schoen Electric & Pump		*			
Did any strata contain unusable water?   Yes  No	(Person, firm or corporation)		ype or pri	nt)		
Type of water? depth of strata	Address 626 W. Queen, Albany	, Or	egon			
Method of sealing strata off	Trans & Selvon					
Was well gravel packed? ☐ Yes X☐ No Size of gravel:	[Signed] (Water Well Conf	_				
Gravel placed fromft. toft.	Contractor's License No. 513 Date	2/2	8	, 19. <i>7</i> 2		
	• • • • • • • • • • • • • • • • • • • •					