NOTICE TO WATER WELL CONTACT TROP IN THE ORIGINAL AND FEB		115	130	-21
STATE ENGINEER, SALEM, OREGON 4730 E ENGINE STATE OF within 30 days from the date SALEM. OR IN fight write a	above this line)			-
(1) OWNER:	(10) LOCATION OF WELL:			
Name Dick Draper /Amigo Acres				
Address 1904 South Main				
Albany, Oregon 97321				
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner			
New Well 🕱 Deepening 🗌 Reconditioning 🗌 Abandon 🗌				
If abandonment, describe material and procedure in Item 12.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well. Depth at which water was first found 18 ft.			
Rotary [] Driven [] Domestic [] Industrial [] Municipal []				
Dug Dered I Irrigation Test Well Other	1. Selow Igin Suitace. Date 1-27-13			
Water Distri	Ctlbs. per square inch. Date			
Threaded □       Welded ½         8       " Diam. from       0         192       ft. Gage       250	(12) WELL LOG: Diameter of well	below ca	sing	8
"Diam. from	Depth drilled 200 ft. Depth of com	pleted wel	1 200	ft.
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,			
(v) PERFORATIONS: Perforated? X Yes INO.	with at least one entry for each change of form position of Static Water Level and indicate pr	nation. Ren	ort each	chanao in
Type of perforator used Mills Knife	MATERIAL	From	То	SWL
Size of perforations 1/4 in. by 4 in.	Soil	0	10	300
1.32 perforations from 1.39 ft. to 188 ft.	Clay (Brown)	1	18	
perforations from ft. to ft.	Sand and Gravel	18	39	20
perforations from ft. to ft.	Sand	39	41	_ <u>~</u>
	Sand and Gravel	41	51	
(1) SCREENS: Well screen installed? 🗌 Yes 🖾 No Manufacturer's Name	Clay (Brown)	51	63	
Type	Sand and Gravel	63	66	
Diam.         Slot size         Set from         ft.         to         ft.	<u>Clay (Gray)</u>	66	80	··
Diam.         Slot size         Set from         ft. to         ft.	Clay (Green)	80	94_	
	Sand (Black) Clay (Gray)	94	95	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	<u>Clay (Gray)</u> <u>Clay (Dark Gray)</u>	95	103	
Was a pump test made? 🗌 Yes 🔰 No If yes, by whom?	Sand (Black)	1.03	119 127	5
Yield: gal./min. with ft. drawdown after hrs.	Sand and Gravel	127	1.90	
" " " " " "	Clay (Gray)	190	200	
	· · · · · · · · · · · · · · · ·			
Bailer test 80 rol (min mill 5 m 2				
Survival 2 2 11. drawdown arter ~ nrs.				· ,
g.p.m. g.p.m. g.p.m. g.p.m. ft.				
perature of water <i>ff</i> Depth artesian flow encountered ft.	Work started 1-11 1973 Comple	ted 1-29		1973
(9) CONSTRUCTION:	Date well drilling machine moved off of well	1-29		1973
Well seal-Material usedCement	Drilling Machine Operator's Certification	:		
Well sealed from land surface to86	This well was constructed under my	direct	super	vision.
Diameter of well bore to bottom of seal in.	Materials used and information reported above are true to my best knowledge and <u>belief</u> .			
Diameter of well bore below seal	10 1/2 1/2 1/2 22			
Number of sacks of cement used in well seal	(Drilling Machine Operator)			
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.			
Brand name of bentonite	Water Well Contractor's Certification:			· · ·
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is			
of water Ibs./100 gals. Was a drive shoe used? 🕅 Yes 🗋 No Plugs Size: location ft.	true to the best of my knowledge and balief			
Did any strata contain unusable water? [] Yes 🖄 No	Name <u>Schoen Electric and Pump</u> (Person, firm or corporation) (Type or print)			
	(Person, firm or corporation) (Type or print)			
Method of sealing strata off	Address 626 W. Queen/ Albant, Oregon 97321			
Was well gravel packed?  Vas Kan No Size of gravel:	[Signed] Janu C. Jahola (Water Well Contractor)			
Gravel placed from ft. to ft.				
			SP	*45658-119