The original and first confidence of this report are to be filled with the JAN 17 1972 STATE OF OREGON

State Well No. .

State Permit No.

STATE ENGINEER, SALEM, OREGON 27310. ENGINEEPRise type or print) within 30 days from the dath A TE SALEM OR COO dot write above this line) of well completion. (10) LOCATION OF WELL: (1) OWNER: R nchero Acres c/o Dick Draper Driller's well number Name Address -1904 S. Marion, A, bany, Oregon NE 14 NE 14 Section 23 T. 11S R. Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well Deepening [Reconditioning [Abandon [If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Rotary Driven 🗆 Static level 7 ft. below land surface. Date Domestic | Industrial | Municipal | Cable Jetted 🔲 Irrigation | Test Well | Other Bored | Artesian pressure lbs. per square inch. Date Dug CASING INSTALLED: Threaded | Welded K (12) WELL LOG: Diameter of well below casing 8 " Diam. from 0 ft. to 189 ft. Gage .250 ft. Depth of completed well Depth drilled 200 " Diam. from _____ft. to _____ft. Gage _____ Formation: Describe color, texture, grain size and structure of materials; " Diam, from _____ ft. to ____ ft. Gage ____ and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? X Yes No. GWT. Type of perforator used Malls Knife 16 Grey clay in. by 3 Size of perforations 43 16 105 perforations from 128 ft. to 140 ft. Small gravel /17 162 ft. to 172 ft. Brown clay 60 perforations from Fine sand with green clay st perforations from _____ ft. to _____ ft. 50 streaks 84 (7) SCREENS: Well screen installed? | Yes | No Fine black sand Manufacturer's Name Black sand with small pea 24 95 gravel Diam. Slot size Set from ft. to ft. 95 Green clay 100 Diam. Slot size Set from ft. to ft. Fine silty sand 100 Grey coarse sand with caorse Drawdown is amount water level is lowered below static level (8) WELL TESTS: 140 115 Fine sand and gravel mixed Was a pump test made? X Yes \(\subseteq \) No If yes, by whom? Schoen 140 with Clay Yield: 200 gal./min. with 30 ft. drawdown after 48 hrs. 154 156 Clay & fine sand 156 172 Coarse sand & gravel 172 189 Fine silty sand & clay ft. drawdown after Bailer test gal./min. with Blue clay 200 Artesian flow g.p.m. 11/26 1971 Completed 1971 perature of water 54 Depth artesian flow encountered ft. Work started Date well drilling machine moved off of well (9) CONSTRUCTION: Drilling Machine Operator's Certification: Well seal—Material used _____Cement This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. Diameter of well bore to bottom of seal ______in. 1977 Diameter of well bore below seal Number of sacks of cement used in well seal Drilling Machine Operator's License No. ... Number of sacks of bentonite used in well seal sacks Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is lbs./100 gals. true to the best of my knowledge and belief. Name Schoen Electric & Pump

(Type or print) (Type or print) Was a drive shoe used? X Yes □ No Plugs Size: location ft. Did any strata contain unusable water?

Yes X No 626 W. Queen, Afbany, Oregon Type of water? Method of sealing strata off (Water Well Contract Was well gravel packed?

Yes X No Size of gravel: Contractor's License No. 513 Date

Gravel placed from _____ ft. fo ____ ft.