

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

LINN
7514

WATER WELL REPORT

STATE OF OREGON
(Please type or print)

RECEIVED

OCT 21 1974 State Well No. 11513W-29

STATE ENGINEER
SALEM, OREGON State Permit No.

(Do not write above this line)

(1) OWNER:

Name Joe E. Kranda
Address SF Columbus 6653 S.E.
Albany, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
 Bored Domestic Industrial Municipal
Irrigation Test Well Other

(4) PROPOSED USE (check):

(5) CASING INSTALLED:

Threaded Welded
6" Diam. from +06" ft. to 94'11" ft. Gage 17#
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.
Type of perforator used Acetylene Torch
Size of perforations 3/8 in. by 12 in.
36 perforations from 85'07" ft. to 94'11" ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
d: gal./min. with ft. drawdown after hrs.
" " " " " "
" " " " " "
Baller test 50 gal./min. with 19 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Bentonite
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal 4 sacks
Brand name of bentonite Oregon Bentonite
Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Linn Driller's well number
1/4 1/4 Section 29 T. 11S R. 3W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 62 ft.
Static level 16 ft. below land surface. Date 10-1-74
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6"
Depth drilled 100 ft. Depth of completed well 100 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	1	
Brown Clay	1	15	
Blue Clay	15	17	
Brown Clay & Gravel	17	60	
Dirty Sand & Gravel	60	67	
Black Silty Clay	67	88	
Sand & Gravel	88	93	
Grey Clay	93	100	

Work started 9-25 1974 Completed 10-1 1974
Date well drilling machine moved off of well 10-1 1974

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Merle Warren Date 10-1, 1974
(Drilling Machine Operator)

Drilling Machine Operator's License No. 313

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Merle Warren Well Drilling
(Person, firm or corporation) (Type or print)

Address RT 1, Box 84, Tangent, Ore. 97389

[Signed] Merle Warren
(Water Well Contractor)

Contractor's License No. 182 Date 10-1, 1974