

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON NOV 14 1972

(Please type or print)

(Do not write above this line)

RECEIVED
STATE ENGINEER
SALEM, OREGON

State Well No. 125/2W-2

State Permit No.

(1) OWNER:

Name Louis Shephard
Address 165 Airport Rd Lebanon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Cable Dug
Driven Jetted Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
8" Diam. from 0 ft. to 3 ft. Gage 1,250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No
Type of perforator used Forch
Size of perforations 1/4 in. by 6 in.
80 perforations from 20 ft. to 30 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: 300 gal./min. with 5 ft. drawdown after 1 hrs.
" " " " "
" " " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 8 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Linn Driller's well number
1/4 1/4 Section 2 T. 12S R. 2W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 20 ft.
Static level 15 ft. below land surface. Date 10-25-72
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8"
Depth drilled 36 ft. Depth of completed well 36 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Brown Top Soil	0	2	
Brown Clay	2	4	
Brown Clay & Gravel	4	13	
Yellow Clay	13	19	
Sand & Gravel	19	29	
Cemented Sand & Gravel	29	33	
Blue Clay	33	36	

Work started 10-20 19 72 Completed 10-25 19 72
Date well drilling machine moved off of well 10-25 19 72

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Jerald J. Munter Date 10-25, 1972
(Drilling Machine Operator)

Drilling Machine Operator's License No. 984

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Josias Drilling Co. Inc
(Person, firm or corporation) (Type or print)
Address St. Rta Box 120 Lebanon

[Signed] Butler (Water Well Contractor)

Contractor's License No. 514 Date 10-25, 1972