

The original and first copy of this report are to be filed with the

RECEIVED

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

SEP 16 1975

Linn 7774

State Well No. 125/20-10

State Permit No.

WATER RESOURCES DEPT.

(1) OWNER: SALEM, OREGON

Name Lebanon Union High School Address Dist UH-1, Lebanon, Ore. 97355

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: (4) PROPOSED USE (check):

Rotary [] Driven [] Cable [X] Jetted [] Dug [] Bored [] Domestic [] Industrial [] Municipal [] Irrigation [X] Test Well [] Other []

CASING INSTALLED:

8" Diam. from +11" ft. to 76'02" ft. Gage 250 Wall

PERFORATIONS:

Type of perforator used Acetylene Torch Size of perforations 1/2 in. by 12 in. 65 perforations from 64'08" ft. to 76'02" ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [X] No Yield: gal./min. with ft. drawdown after hrs. Bailer test 88 gal./min. with 25 1/2 ft. drawdown after 2 hrs.

(9) CONSTRUCTION:

Well seal-Material used Bentonite & Cement Well sealed from land surface to 20 ft. Diameter of well bore to bottom of seal 12 in. Diameter of well bore below seal 8 in. Number of sacks of cement used in well seal 2 1/2 sacks Number of sacks of bentonite used in well seal 3 sacks Brand name of bentonite Volclay Number of pounds of bentonite per 100 gallons of water Was a drive shoe used? [X] Yes [] No Plugs Size: location ft. Did any strata contain unusable water? [] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Linn Driller's well number 1/4 Section 10 T. 12S R. 2W W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 20 ft. Static level 10'06" ft. below land surface. Date 7-25-75 Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 8"

Depth drilled 76 ft. Depth of completed well 76 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Top Soil, Br. Clay & Large Gravel, Dirty Gravel, Brown Clay & Gravel, Dark Brown Clay, Brown Clay & Coarse Grav, Dirty Brown Sand & Grav., Brown Clay & Gravel.

Work started 7-21 19 75 Completed 7-25 19 75 Date well drilling machine moved off of well 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Date 7/28, 1975 Drilling Machine Operator's License No. 436

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name Merle Warren Well Drilling Address Rt. 1, Box 84, Tangent, Ore. 97389 [Signed] Merle Warren Contractor's License No. 182 Date 7-28, 1975