NOTICE TO WATER WELL CONTRACTOR 19 1966

The original and first copy of this report are to be 1 TE ENGIWATER WELL REPORT filed with the

11111 8234		12/2	tu -2	マk
State	Well No.	16/2	.W ~Z	ی ر

STATE ENGINEER, SALEM, OREGON 97316 M OREGON (Please type or print) of well completion.

G-3715

State Permit No.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level of
Name Cowbot School 87C	Was a pump test made? Yes [No If yes, by whom? Rannsey Warle
Address Cascale Dr.	Yield: 120 gal./min. with 49ft. drawdown after 3 hrs.
Lebanon Chegon	" " " "
(2) LOCATION OF WELL: √	" " " "
County 2 Mn Driller's well number	Bailer test gal./min. with ft. drawdown after hrs.
County Sun Driller's well number, 1/4 Section & 3 T. 12 S R. 2W W.M.	Artesian flow g.p.m. Date
Bearing and distance from section or subdivision corner	Temperature of water 52 Was a chemical analysis made? Yes No
bearing and distance from section of subdivision corner	(12) WELL LOG: Diameter of well below casing
	Depth drilled 8 / ft. Depth of completed well 8 / ft.
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each
	show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
	MATERIAL FROM TO
(3) TYPE OF WORK (check):	A 11/2 Silver to the second se
Well Deepening ☐ Reconditioning ☐ Abandon ☐	marcy said
A sandonment, describe material and procedure in Item 12.	10 10 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
	Band gravel + clay 10 81
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Went I had Parked
Domestic Industrial Municipal Rotary Driven Cable Jetted	1000 1000 1000 X5 53
Irrigation Test Well Other Dug Bored	sand + angul 53 65
(6) CASING INSTALLED: Threaded Welded	Clay Dand + Vanuel 65 68
/D "Diam. from 0 ft. to 86 ft. Gage 250	tight
"Diam. from ft. to ft. Gage ft	Dand + grand 1 88 80
"Diam. fromft. Gage	Rand grand + Clay 50 81
(7) PERFORATIONS: Perforated? ☐ Yes No	01 9 3
Type of perforator used	1 Ph. 112-
Size of perforations in. by in.	hushness 4 gr.
perforations from ft. to ft.	- radarios 10
perforations from ft. to ft.	Jun hone
perforations from ft. to ft.	Visable
perforations from ft. to ft.	
(8) SCREENS: Well screen installed?	
, , , , , , , , , , , , , , , , , , ,	
Manufacturer's Name	
Dram. Slot size Set from ft. to ft.	
Diam, Slot size Set from ft. to ft.	Work started 6 - 2.0 1966 Completed 1 - 17 1966
	Date well drilling machine moved off of well 7-14 1956
(9) CONSTRUCTION:	(13) PUMP:
Well seal—Material used in seal	Manufacturer's Name
Depth of seal2_()ft. Was a packer used?	Туре: Н.Р.
Diameter of well bore to bottom of seal in.	Water Well Contractor's Certification:
Were any loose strata cemented off? Yes No Depth	Waver Weir Contractor's Certification.
Was a drive shoe used? Yes ☐ No	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was well gravel packed? Yes No Size of gravel:	94'10 a H
Gravel placed from ft. to ft.	NAME Stillamette Grayation & Luy Co
Did any strata contain unusable water? Yes X No	Address Sas Rut #2 Bit S Lelianin
Type of water? depth of strata	Audi 600 Material Parkage
Method of sealing strata off	Drilling Machine Operator's License No.
(10) WATER LEVELS:	Issued Call & Any deep
Static level 2/ ft. below land surface Date 2/4-64	[Signed] (Water Well Contractor)
Artesian pressure lbs. per square inch Date	Contractor's License No. 2 Date
	, , , , , , , , , , , , , , , , , , , ,