NOTICE TO WATER WELL CONTRACTOR. 6

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON, 97810 E ENGINEERS type or print) of well completion.

C6834 State Permit No.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level		
Name Jack Kalina	Was a pump test made? Yes K No If yes, by who		i na grafik pe <del>ran</del> g
Address Rt. 3, Box 917B	Yield: gal./min, with ft. drawdov	<del></del>	hrs.
Albany, Oregon	" "	1 1.	
(2) LOCATION OF WELL:	" " "		,,
County Linn Driller's well number	Bailer test 100 gal./min. with 10 ft. drawd	own after	l hrs.
14 17S 4W	Artesian flow g.p.m. Date		
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis	made? 🔲 🖰	Yes K No
bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below ca		
	Depth drilled 200 ft. Depth of completed we		
	Formation: Describe by color, character, size of materic show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each c	l and stru the mater	cture, and al in each
	stratum penetrated, with at least one entry for each c	nange of	formation.
(3) TYPE OF WORK (check):	MATERIAL	FROM	TO
Well <b>M</b> Deepening □ Reconditioning □ Abandon □	Top Soil	0	
andonment, describe material and procedure in Item 12.	Brown Clay	2	14
	Blue Clay	14	<del>-25</del> -
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Gravel	25	<del>-35</del>
Domestic K Industrial   Municipal   Rotary   Driven	Black Sand	35	<del>-43</del> -
rrigation K Test Well  Other Dug Bored	Grey Clay	43	<del>82</del>
(C) CACING INCHALLED	Shale	82	173
Interded   Welded In	Shale & sm pcs blk	<u> </u>	
	l rock	173	<del>-175-</del>
ft. to ft. Gage	Grey Shale	175	<del>-200</del> -
" Diam. from ft. to ft. Gage		<u> </u>	
(7) PERFORATIONS: Perforated  Yes   No		<u> </u>	
Type of perforator used		1	
Size of perforations 3/8 in. by 12 in.		-	
38 perforations from 2910811 ft. to 4010811 ft.			<del></del> .
perforations fromft. toft.		-	
perforations from ft. to ft.		-	
perforations from ft. to ft.		<del>                                     </del>	
perforations from		<del>  -  </del>	<u></u> <u> 7</u>
O) CODETAG			<u> </u>
won borden mistaneur   Tes   19110			<del></del>
Manufacturer's Name			
Model No.		<del></del>	
Tam. Slot size Set from ft. to ft.	Work started 11-16 19 65 Completed 11	-30	1965
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well		
9) CONSTRUCTION:	(13) PUMP:	0	<sup>19</sup> 65
Vell seal—Material used in sealBentonite	Manufacturer's Name	*	er i sirj
Depth of seal	Туре:	T D	
Diameter of well bore to bottom of seal 14 in.			
Vere any loose strata cemented off? ☐ Yes X☐ No Depth	Water Well Contractor's Certification:	,	
Vas a drive shoe used? Ä Yes □ No	This well was drilled under my jurisdiction a	and this	renort is
Vas well gravel packed? 🗌 Yes 🏋 No 💮 Size of gravel:	true to the best of my knowledge and belief.		
ravel placed from ft. to ft.	NAMEMerleWarren Well Drillin		
Did any strata contain unusable water? 🗌 Yes 🙀 No	(Person, firm or corporation) (Type or print)		
ype of water? depth of strata	Address Rt. 1, Box 85, Tangent, Oregon		
Iethod of sealing strata off			
10) WATER LEVELS:	11/04/1/12		
tatic level ft. below land surface. Date	[Signed] / flue Warren	<i></i>	
20 20 11-30-6 B	(Water Well Contractor)	1-2 1	/
rtesian pressure lbs. per square inch Date	Contractor's License No. 182 Date	30	19.65