NOTICE TO WATER WELL CONTRACTOR: OF UE

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97810 TE ENGINEER STATE OF OREGON within 30 days from the date.

of well completion. CALFM OREGON	G-3744 State Permit No	••••••	
1) OWNER:	(11) WELL TESTS: Drawdown is amount v lowered below static lev	vater leve vel	el is
ame Ed Roberts	Was a pump test made?  Yes No If yes, by whom	?	
ddress Rt. 3	Yield: gal./min. with ft. drawdow	n after	hrs.
Albany, Oregon	" "		
2) LOCATION OF WELL:	n n		. "
2) HOCKITON OF WELLS.	Bailer test QO gal./min. with 4 ft. drawdo	wn after	7 hrs.
county Linn Driller's well number	Artesian flow g.p.m. Date	-	:
¾ ¾ Section 15 Т. 11S R. 4W W.M.	Temperature of water Was a chemical analysis n	nade? 🔲 🕽	Yes 🏋 No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below case		811
	(12) WELLE LIOU. Diameter of Well below cas	ang	
	Depth drilled 58 ft. Depth of completed wel	1 1	58 ft.
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of t stratum penetrated, with at least one entry for each ch	and stru he mater lange of	cture, and ial in each formation.
	MATERIAL	FROM	то
3) TYPE OF WORK (check):		<del></del>	4
· •	Top Soil	0	
Well Deepening ☐ Reconditioning ☐ Abandon ☐	Brown Clay	4	_15
handonment, describe material and procedure in Item 12.	Blue Clay	15	
4) PROPOSED USE (check): (5) TYPE OF WELL:	Clay & Gravel	30	48
Rotery □ Driven □	Black Sand & Gravel	48	_58
Omestic ☐ Industrial ☐ Municipal ☐ Cable X Jetted ☐ rrigation 🔏 Test Well ☐ Other ☐ Cable X Jetted ☐			
Dug Bored		1	
(6) CASING INSTALLED: Threaded Welded			
8		1	
" Diam from ft. to ft. Gage			
"Diam. fromft. toft. Gage			
(7) PERFORATIONS: Perforated? Yes   No		1	
Type of perforator used Acetylene Torch			
Size of perforations ½ in, by 12 in.			
38 perforations from 45 10" ft. to 56 10" ft.	•		124.
ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
(0) COPERIG.		1	
(8) SCREENS: Well screen installed? ☐ Yes 🛣 No			
Manufacturer's Name			
Model No.			
n Slot size Set from ft. to ft.	Work started 7-22 19 66 Completed 7	7-25	19 66
Diam Slot size Set from ft. to ft.	Date well drilling machine moved off of well 7-2	<u>2</u> 6	19.66
(9) CONSTRUCTION:	(13) PUMP:		
` '	(15) 1 01/11		
Well seal—Material used in sealBentonite	Manufacturer's Name		
Depth of seal8 ft. Was a packer used?	Type:	H.P	
Diameter of well bore to bottom of seal12 in.	Water Well Contractor's Certification:		
Were any loose strata cemented off? ☐ Yes ¾ No Depth	water wen contractor's Certification.		
Was a drive shoe used? ∰Yes □ No	This well was drilled under my jurisdiction	and this	report is
Was well gravel packed? ☐ Yes X No Size of gravel:	true to the best of my knowledge and belief.		
Gravel placed from ft. to ft.	NAME Merle Warren Well Drilli	ing	
Did any strata contain unusable water? ☐ Yes X☐ No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address Rt. 1. Box 85, Tangent, Oregon		
Method of sealing strata off	73	13	esservice of the second
	Drilling Machine Operator's License No3.	-A	······································
(10) WATER LEVELS:	[Signed] // Warre	<i>ye</i>	-
Static level 25 ft. below land surface Date 7-25-66	(Water Well Contractor)	/	
Artesian pressure lbs. per square inch Date	Contractor's License No. 182 Date	28	, 19 <b>66</b>
Francis English and Franci	1 Correspond procupe riot numerous Sand minimum		