NOTICE TO WATER WELL CONTRAC'D.

The original and first copy
of this report are to be filed with the

Number of sacks of cement used in well seal .

Number of sacks of bentonite used in well seal .. Brand name of bentonite Oregon Bentonite

Number of pounds of bentonite per 100 gallons

Was a drive shoe used? 💥 Yes 🗌 No Plugs

Did any strata contain unusable water? 🔲 Yes 🟋 No

depth of strata

Size of gravel:

of water

Type of water?

Method of sealing strata off

Gravel placed from

Was well gravel packed? ☐ Yes XNo

2				•	
23	ř,	State	Well	No.	-44/.
.	. 17	: .t	بر	*****	/

STATE ENGINEER, SALEM, OREGON FIAOTE ENGINEER, type within 30 days from the date of well completion.	or print) State Permit N TO A TO A	0.
(1) OWNER:	(10) LOCATION OF WELL:	LINN
Name Dr. Donald Boye Address Rt. 3, Pirtle Dr., Albany, Ore. 97321	County Driller's well m 14 Section 23 T. 11S	R. 4W W.M.
(2) TYPE OF WORK (check): New Well Deepening Reconditioning Abandon Abandon If abandonment, describe material and procedure in Item 12.	Bearing and distance from section or subdivisi	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed w Depth at which water was first found 30	** ** **. **. **. **. **. **. **. **. *
Rotary ☐ Driven ☐ Domestic ☐ Industrial ☐ Municipal ☐ Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Static level 20 ft. below land s Artesian pressure lbs. per squar	surface. Date 17-70 re inch. Date
CASING INSTALLED: Threaded Welded 20 Welded 20 Welded 25 Wall	(12) WELL LOG: Diameter of well to	pelow casing
"Diam from ft. to ft. Gage ZDUNAII	Depth drilled 60 ft. Depth of compl	eted well 60 ft.
" Diam. fromft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratus with at least one entry for each change of formation of Static Water Level and indicate print	m and aquifer penetrated, tion. Report each change in
of perforator used Acetylene Torch	MATERIAL	From To SWL
Size of perforations ½ in. by 12 in.	Top Soil	0 1
60 perforations from 42 ft. to 54 ft.	Brown Clay	1 17 -
perforations from ft. to ft.	Dark Blue Clay	17 22
perforations fromft. toft.	Black Clay	22 27
(7) SCREENS: Well screen installed? Yes Y No	Dirty Gravel	27 30
(1) SCREENS: Well screen installed? ☐ Yes X☐ No Manufacturer's Name	Black Sand & Gravel	30 34
Type Model No.	Black Sandy Clay	34 35
Diam. Slot size Set from ft. to ft.	Washed Coarse Gravel &	35 51
Diam. Slot size Set from ft. to ft.	Black Sand	
	Blue Clay	51 60
(8) WELL TESTS: Drawdown is amount water level is lowered below static level Stettler		
Was a pump test made? ★□ Yes □ No If yes, by whom? Supply		Section 1997 Section 1997
Yield: 190 gal./min. with 35 ft. drawdown after 3 hrs.		
" " " "	Figure 1 and	
" " "	A CONTRACTOR OF THE PROPERTY O	
Bailer test 100 gal./min. with 5 ft. drawdown after 11/2 hrs.	The second secon	
	A STATE OF THE STA	
	0_16 70	ed 9-17 19 70
Temperature of water Depth artesian flow encountered		70
CONSTRUCTION:	Date well drilling machine moved off of well	9-17 197 -
Well seal—Material used Bentonite Well sealed from land surface to 18 ft. Diameter of well bore to bottom of seal 1.4 in.	Drilling Machine Operator's Certification: This well was constructed under my Materials used and information reported best knowledge and belief.	direct supervision. above are true to my
Diameter of well bore below seal in.	[Signed] (Drilling Machine Operator)	Date 9-19, 19.70

Water Well Contractor's Certification:

Drilling Machine Operator's License No.

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name	Merte	Warren	METT	υr:	TTTJ	.ng
ivaliic .	(Person	n, firm or co	rporation)			(Ty)

Address	Rt. 1. F	30x 84.	Jangent,	Ore.	97389	
777	VVI 1	رنك	V			
	-	1	MAKEN	- '		

7	(Water	Well Con	ntractor)	
/	1 de	117	0-	-
ontractor's License No	182	Date	7	L

lbs./100 gals.

Size: location