NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

## STATE OF OREGON

(Please type or print) (Do not write above this line) FINN

State Well No. 115/5W - 36

State Bermit No. G-9280

APPL. G-9689

(1) OWNER:	(10) LOCATION OF WELL:	_
Name HARRY LAGERSTEST T	County LINN Driller's well number 79-6	
Address 1700 NW. KINGS BLUD.	1/4 Section, 3/4 T. // R., 5 W.M.	
CORUALIZA SEC. 92330	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well   Deepening □ Reconditioning □ Abandon □  Reconditioning □ Abandon □		_
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	ft.
Rotary Driven Domestic Domestic Municipal Domestic Municipal	Static level 2 / ft. below land surface. Date 6/25	1/79
Dug   Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square inch. Date	<i>F</i> ' '
CASING INSTALLED: Threaded Welded Good Diam. from 6 ft. to 4 ft. Gage 250		プ/ ft.
PERFORATIONS: Perforated? V Yes \( \sigma\) No.	Formation: Describe color, texture, grain size and structure of materia and show thickness and nature of each stratum and aquifer penetrate with at least one entry for each change of formation. Report each change position of Static Water Level and indicate principal water-bearing stra	ed, in
Type of perforator used MIIIS KNIFE	MATERIAL From To SWL	,
Size of perforations 3/4 in. by 4/ in.	CLAY-BROWN 0' 3'	
perforations from 34 ft. to 35 ft.	CLAY-BROWN +	
perforations from 35 ft. to 36 ft.	SAND BIALK 3'31'	<u> </u>
perforations fromft. toft.	COMENTED SAND 3134	
(7) SCREENS: Well screen installed?   Yes  No	GRAVE! medium	<del>-</del> ,
Manufacturer's Name	COATER ISCAPING SYS / 2	<u> </u>
Type Model No.	CLAY-BLUES WELLS	
Diam Slot size Set from ft. to ft.	CS/1/-13/10\ 72 X3 2/	
Diam. Slot size Set from ft. to ft.	·	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	CECEIVIS	
Was a pump test made?  Yes No If yes, by whom?	1111 - 2 1070	
Yield: gal./min. with ft. drawdown after hrs.	- OOL 01073	<del></del> · <del>-</del>
" " "	WATER RESOURCES DEPT	
" " "	SALEM, OREGON	
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
perature of water 5.5 Depth artesian flow encountered ft.	Work started 6/8 19/7 Completed 6/25 19	29
(9) CONSTRUCTION:	Date well drilling machine moved off of well 6/25 19/	19
Well seal-Material used Lene WT	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my direct supervisio Materials used and information reported above are true to m	n. IV
Diameter of well bore to bottom of seal in.	best knowledge and belief	
Diameter of well bore below sealin.	[Signed] Advis Saula II Date 5/20, 19	<u> </u>
Number of sacks of cement used in well seal sacks  How was cement grout placed?	Drilling Machine Operator's License No	
CEMENT PIACES TROM		_
DI' TO LAND SURYACE	Water Well Contractor's Certification:	
method-15	This well was drilled under my jurisdiction and this report true to the best of my knowledge and belief	is
Was a drive shoe used? Yes 🗆 No Plugs Size: location ft.		<i>-</i>
Did any strata contain unusable water?   Yes No	(Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address 28827 Hy 34 CORUA IIIS	_ORE
Method of sealing strata off	[Signed] Robert & Carlos II	
Was well gravel packed?   Yes No Size of gravel:	(Water Well Contractor)	
Gravel placed fromft. toft.	Contractor's License No. 54 Date 5/30 19	<u> </u>