

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Write above this line)

LINN 9115

State Well No. 12/W-702

State Permit No.

RECEIVED SEP 25 1969 STATE ENGINEER SALEM, OREGON

(1) OWNER:

Name J. D. GRIFFITH Address 990 RIVER, Lebanon, Ore.

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven [] Cable [x] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [x] Test Well [x] Other []

CASING INSTALLED:

8" Diam. from 1 ft. to 83 ft. Gage 250

(6) PERFORATIONS:

Perforated? [] Yes [x] No. Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 18'6" ft. below land surface Date 9-23-69

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level. Was a pump test made? [] Yes [x] No. Yield: gal./min. with ft. drawdown after hrs. Down with compressor, 600 CFM, 125 PSI. Better test approx 300 gal./min. with 80 ft. drawdown after 5 hrs. Artesian flow g.p.m. Date Temperature of water 57° Was a chemical analysis made? [] Yes [x] No

(10) CONSTRUCTION:

Well seal—Material used CEMENT & BENTONITE Depth of seal SURFACE SEAL 18'; 2nd seal 20' in. Diameter of well bore to bottom of seal 11 in. Were any loose strata cemented off? [] Yes [x] No Depth Was a drive shoe used? [] Yes [x] No Did any strata contain unusable water? [] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County LINN Driller's well number SE 1/4 SW 1/4 Section 7 T. 12 S R. 1 W W.M. Bearing and distance from section or subdivision corner 190°E, 1150N; SW CORNER Sec 7

(12) WELL LOG:

Diameter of well below casing 8" to 217' 6" from 217-253 Depth drilled 255 ft. Depth of completed well 253 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include SANDSTONE BOTTEN BROWN, SANDSTONE BLUE, CONGLOMERATE BLUE SOFT, AQUIFER, BENTONITE SANDUST, CONGLOMERATE BLUE HARD, AQUIFER CRYSTALS BENTONITE, HARD BLUE FORMATION, MORE BENTONITE SANDUST, CONGLOMERATE BLUE.

Work started 9-3-1969 Completed 9-23-1969 Date well drilling machine moved off of well 9-24-1969

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] [Signature] Date 9-24, 1969 (Drilling Machine Operator)

Drilling Machine Operator's License No. 91

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME [Signature] (Type or print)

Address RT. 3, Box 427, Lebanon, Ore.

[Signed] [Signature] (Water Well Contractor)

Contractor's License No. 266 Date 9-24, 1969