NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 973 within 30 days from the data within 30 days from the date of well completion.

WATER WELL REPORT CEIVED
STATE OF OREGON JUL 1 0 1975 State Well No. 125/14-28

(Please type or print) TER RESOURCES SEPTERMIT No. (Do not write above this line AI FM OREGON

ν	SALEM, OREGUN
(1) OWNER:	(10) LOCATION OF WELL:
Name Linn County Parks & Rec. Dept.	County Linn Driller's well number
Address PO Box 100, Albany, Orc. 97321	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well	
If abandonment, describe material and procedure in Item 12.	(11) WATED TEVEL Completed well
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well. Depth at which water was first found 34 ft.
Rotary Driven Domestic L Industrial Municipal D	Static level 10 ft. below land surface. Date 5-30-75
Cable X Jetted Doneste La Industrial Industrial Dug Bored Irrigation Test Well Other Dug D	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded X	(10) TURN I I O C
_6	(12) WELL LOG: Diameter of well below casing
"Diam. from ft. to ft. Gage ft	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Acetylene Torch	MATERIAL From To SWL
Size of perforations 3/8 in. by 12 in.	Top Soil 0 2
	Sand 2 3
ft. to ft.	Sand & Gravel 3 6
perforations from ft. to ft.	Gravel & Boulders 6 12
(7) SCREENS: Well screen installed? Yes 53 No	Boulders 12 34
· · · · · · · · · · · · · · · · · · ·	Sand & Gravel 34 38
Manufacturer's Name	Gravel 38 40
Type Model No Diam Slot size Set from ft. toft.	Blue Sand
Diam. Slot size Set from ft. to ft.	Gravel 48 51
200 200 200 200 200 200 200 200 200 200	7.
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? 🗌 Yes 🏋 No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	·
" " " "	
	the state of the s
Bailer test 60 gal./min. with 5 ft. drawdown after 1 hrs.	F
Artesian flow g.p.m. Appearature of water Depth artesian flow encountered ft	
nperature of water Depth artesian flow encountered ft.	Work started 5-28 19 75 Completed 5-30 19 75
(9) CONSTRUCTION:	Date well drilling machine moved off of well 5-30 7
Well seal—Material used Bentonite	Drilling Machine Operator's Certification:
Well sealed from land surface to ft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)
Number of sacks of cement used in well seal sacks	7(0)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 200
Brand name of bentonite <u>Oregon Bentonite</u>	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of water lbs./100 gals.	true to the best of my knowledge and belief.
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft. Manuiactured Did any strata contain unusable water? ☐ Yes ☐ No	Name Merle Warren Well Drilling (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address Rt. 1. Box 84, Tangent, Ore. 97389
Method of sealing strata off	Signed Hastel Washen
Was well gravel packed? ☐ YesX☐ No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 182 Date