NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the WELL WATER WELL WELL WATER WELL	L REPORT MACH 187 16 14 25 02 40
WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 WATER RESOURCES DEPARTMENT. JUN 2 9 198 TATE OF (Please type	OREGON Malh 107 State Well No. 15s/42E-23 ba
within 30 days from the date of well completion. WATER RESOURCES DEPT of well completion.	ove this line) State Permit No.
(1) OWNER:	(10) LOCATION OF WELL:
Name Cra/9 Seddoway	County Maller's well number
Address RANGAN OFE.	N.C. 14N W 14 Section J. 3 T. 15 Sta. 42 E. W.M.
Brod. III	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 125 ft.
Cable Jetted Domestic Industrial Administral	Static level 30 ft. below land surface. Date 4-10-8
Dug	Artesian pressure lbs. per square inch. Date
SASING INSTALLED: Threaded Welded ## Diam. from ft. to ft. Gage 250	(12) WELL LOG: Diameter of well below casing
"Diam. from tt. to ft. Gage	Depth drilled 750 ft. Depth of completed well 750 ft.
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated.
	with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Soil with boulders 0 8
perforations from ft. to ft.	Grown Clay (Sticky) & 20
perforations from ft. to ft.	brown clay, 70 65
perforations from ft. to ft.	Mour clay hard 65 125 20
	Trown Clay 125 190 30
(7) SCREENS: Well screen installed? Yes No	brown Glat Med grave 190 192 30
Manufacturer's Name	from Clay 192 335 30
Type Model No.	from chy (met grand) 335 345 30
Diam. Slot size Set from ft. to ft.	Line grower med in san 345 349 30
Diam. Slot size Set from ft. to ft.	Med Longlomerate with 2110 725
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Prouse clay 375 450 30
Was a pump test made? Yes No If yes, by whom? when	RECEIVED
Yield: 500 gal./min. with 210ft. drawdown after 2 hrs.	
,, ,,	MAY 2 2 1981
" " "	WATER RESOURCES DEPT
Bailer test gal./min. with ft. drawdown after hrs.	SALEM, OREGON
A wtesian flow g.p.m.	
perature of water 1 Depth artesian flow encountered ft.	Work started 2-6 18/ Completed 4. 19 198
(9) CONSTRUCTION:	Date well drilling machine moved off of well 4. 24 198
Well seal-Material used Cortland Coment	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signey General A. Sourmapete 5-18, 198/
Number of sacks of cement used in well sealsacks	(Drilling Machine Moerator)
How was cement grout placed? Pupp	Drilling Machine Operator's License No. 1406
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my helpwiedge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	
Did any strata contain unusable water? Yes No	Name (Pyrson, firm or carporation) (Type or print)
Type of water? depth of strata	Address Say SS ale Const
Method of sealing strata off	2 11 200
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] (Water Well Confractor)
Gravel placed from ft. to ft.	Contractor's License No. 3.96 Date 5- 1954