## WATER WELL REPORT STATE OF OREGON

## RECEIVED

State Well No.

185/45E-23

APR 27 19 PLEASE TYPE or PRINT IN INK

1) OWNER: WATER RESOURCES DEPT.	(10) LOCATION OF WELL:
Name Kirt Adams SALEM. OREGON	County Malheur Driller's well number
Address P.O. Box 221 Ontario, Oregon 97918	
City Ontario State Oregon	Tax Lot # 1801 Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location:
New Well	(11) WATER LEVEL: Completed well.
f abandonment, describe material and procedure in Item 12.	Depth at which water was first found 23 ft
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level 12 ft. below land surface. Date 3/24/
Rotary Air   Driven   Domestic Industrial   Municipal   Dw Mud   Dug   Irrigation Test Well   Other	Artesian pressure lbs. per square inch. Date
v Mud □ Dug □ Irrigation ♣ Test Well □ Other □  X Bored □ Thermal: Withdrawal □ Reinjection □	(12) WELL LOG: Diameter of well below casing12
	Depth drilled 115 ft. Depth of completed well 115 ft
(5) CASING INSTALLED: Steel A Plastic Threaded Welded	Formation: Describe color, texture, grain size and structure of materials; and show
12 "Diam from +1 ft. to 19 ft. Gauge •250	thickness and nature of each stratum and aquifer penetrated, with at least one entr
"Diam. from ft. to ft. Gauge	for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
	MATERIAL From To SWL
LINER INSTALLED:	
(6) PERFORATIONS: Perforated?   ▼ Yes □ No	Gravel 15 28 Blue Sandy Clay 28 35
Type of perforator used Torch	
Size of perforations 4 in. by in.	Blue Clay 35 49 Blue Sandstone 49 70
60 perforations from 18 ft. to 28 ft.	Blue Sand stone pea grav. 70 115
perforations from ft. to ft.	Blue Clay 115
perforations fromft. toft.	Ditte Oray
(7) SCREENS: Well screen installed?   Yes X No	
Manufacturer's Name	
Type Model No	
Diam. Slot Size Set from ft. to ft.	
Diam. Slot Size Set from ft. to ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
a pump test made? X Yes No If yes, by whom?Riverside E]	ectric.
Yield: 75 gal./min. with 93 ft. drawdown after 1 hrs.	
11 " " "	
Air test gal/min, with drill stem at ft. hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
sian flow g.p.m.	
Temperature of water 52 Depth artesian flow encountered ft.	Work started 3/15 19 88 Completed 3/24/ 19 8
(9) CONSTRUCTION: Special standards: Yes □ NoX	Date well drilling machine moved off of well 3/24 19 8
Well seal—Material used Cement	(unbonded) Water Well Constructor Certification (if applicable):
Well sealed from land surface to	This well was constructed under my direct supervision. Materials use
Diameter of well bore to bottom of seal1.6in.	and information reported above are true to my best knowledge and belief
Diameter of well bore below seal12 in.	[Signed] Date, 19
Number of sacks of cement/used in well seal sacks	
How was cement grout placed? Pressure Grouted	Bond U45-8259 Issued by: United Pacific Ins Surety Company Name
	This well was drilled under my jurisdiction and this report is true
	the best of my knowledge and belief.
Was pump installed?	11anc
Was a drive shoe used? X Yes No Plugs Size: location ft.	(Type or print) Address 590-15th. St. N. Vale Oregon 979
Did any strata contain unusable water?   Yes X No	11.00(1)-
Type of Water? depth of strata  Method of sealing strata off	[Signed] Water Well-Constructor
Was well gravel packed? ☐ Yes XNo Size of gravel:	3/2// 2.88
Gravel placed from	, 2000