NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 973 within 30 days from the date of well completion. WATER WELL REPORT CEIVED

STATE OF OREGON AUG 1 1 1975 State Well No. 185/4515 -28

(Please type or print) ER RESOURCES DEPT State Permit No. G-6448 (#1)
(Do not write above this line ALEM, OREGON

		_
(1) OWNER:	(10) LOCATION OF WELL:	
Name HERMAN OLSEN	County MATHEUR Driller's well number	,
Address VALE, OREGON 97918	NE 14 NW 14 Section 28 T. 18 R. 45 W.	M.
	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well 🔀 Deepening 🗍 Reconditioning 🗍 Abandon 🗍		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):		ft.
Rotary 🔲 Driven 🗎 Domestic 😾 Industrial 🗎 Municipal 🔲	Static level 45 ft. below land surface. Date 4-14-7	15
Cable ☑ Jetted ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐	Artesian pressure lbs. per square inch. Date	
(5) CASING INSTALLED: Threaded Welded	Formation: Describe color, texture, grain size and structure of materia	
AN DEDECT A BLONG.	and show thickness and nature of each stratum and aquifer penetrate with at least one entry for each change of formation. Report each change position of Static Water Level and indicate principal water-bearing stra	e in
(6) PERFORATIONS: Perforated? Yes No.	MATERIAL From To SWI	
1 0/6/	SANDY SOIL 0 1	
	SANDSTONE MED. PEBBLES 1 4	
40 perforations from 55 ft. to 60 ft.	STICKY LT. BRN. CLAY & MED S.S. 4 16	_
perforations fromft. toft.	STICKY BROWN CLAY 16 53	
perforations fromft. toft.	CONGLOMERATE STONE 53 57	
(7) SCREENS: Well screen installed? Yes D No	MED. GRAVEL W/B 57 60 45	
Manufacturer's Name	BLUE CLAY 60 61	
Type Model No		
Diam Slot size Set from ft. to ft.		
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ☐ Yes ☐ No If yes, by whom?		
Yald: gal./min. with ft. drawdown after hrs.		
	the state of the s	
n " " "		
Bailer test 34 gal./min. with 6 ft. drawdown after 1 hrs.		
Artesian flow g.p.m.		
perature of water 601 Depth artesian flow encountered ft.	Work started 4-12-75 19 Completed 4-14-75 19	
(9) CONSTRUCTION:	Date well drilling machine moved off of well 4-14-75 19	
Well seal—Material used CEMENT GROUT	Drilling Machine Operator's Certification:	~ ~
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to be	my
Diameter of well bore to bottom of seal9	hest knowledge and helief	
Diameter of well bore below seal	[Signed] Archie W. Date 4-14-75, 19 (Drilling Machine Operator) 729	
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No. 729	
Number of sacks of bentonite used in well seal sacks	Drining Machine Operator's Electibe 140.	
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report	t i
of waterlbs./100 gals.	true to the best of my knowledge and belief.	
Was a drive shoe used? ▼ Yes □ No_Plugs Size: location ft.	Name PAGE BROS DRILLING (Person, firm or corporation) (Type or print)	
Did any strata contain unusable water? Yes No	· · · · · · · · · · · · · · · · · · ·	
Type of water? depth of strata	Address RT. 1 BOX 371 VALE OREGON 97918	
Method of sealing strata off	[Signed] My (Water Well Contragor)	
Was well gravel packed? Yes No Size of gravel:	Contractor's License No. 564 Date 4-14-75 19	
Gravel placed from ft. to ft.	Contractor's Literise Ivo	