NOTICE TO WATER WELL CONTRET TO EIVER The original and first copy of three ert CEIVERTER WEI are to be filed with the	L REPORT	in line to l
WATER RESOURCES DEPARTMENTJAN221979 STATE OF	OREGON State Well No.	185/47E-7cd
	or print)	
SALEM, OREGON 97310 SATING TO THE SALEM, OREGON 97310 within 30 days from the date of well completion WATER RESOURCES DEPT. SALEM. OREGON	pove this line).	0
(1) OWNER;	(10) LOCATION OF WELL:	
Name amilda Kano	County MALHE UR Driller's well number	
Address ANTALAL AL	SE 45W 4 Section 7 T. 18SR. 47E W.M.	
	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		Jir corner
New Well 🗗 Deepening 🗌 Reconditioning 🗌 Abandon 🗌		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	36 ft.
Rotary □ Driven □ Cable □ Jetted □ Domestic □ Industrial □	Static level J ft. below land surface. Date Artesian pressure Ibs. per square inch. Date	
Dug Bored I Irrigation I Test Well D Other		
CASING INSTALLED: Threaded D Welded	(12) WELL LOG: Diameter of well below casing /6	
for "Diam. from for the to O ft. Gage the	(12) WELL LOG: Diameter of well below casing <u>16</u> Depth drilled <u>10</u> <u>5</u> ft. Depth of completed well <u>10</u> <u>5</u> ft.	
	Formation: Describe color, texture, grain size and structure of materials;	
"Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated.	
PERFORATIONS: Perforated? Ves I No.	with at least one entry for each change of format position of Static Water Level and indicate prin	ion. Report each change in cipal water-bearing strata.
Type of perforator used TN RCH	MATERIAL	From To SWL
Size of perforations 3/1/6 in. by 6 in.	Soil GRANNI	03
13.0 perforations from 3.0 tt. to A.O. tt.	CLAU BROUN	3 18
	CLAUBLUC.	18 36
perforations from ft. to ft.	SANDTGRAVEL	3654 24
(7) SCREENS: Well screen installed? Yes You	- CLA YSANdy WATCH	54 93 34
Manufacturer's Name	- CLAYBLUESANdy	93103 24
Type Model No		
Diam Slot size Set from ft. to ft.		
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? Ves I No If yes, by whom PRI//er	P1,	
reld: 97 gal./min. with 80 ft. drawdown after 9 hrs.		
	· · · · · · · · · · · · · · · · · · ·	
<u> </u>		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow i g.p.m.		
inperature of water 5.5 Depth artesian flow encountered ft.	Work started / 3 - 8 197 Scomplete	1/2-14 1878
(9) CONSTRUCTION:	Date well drilling machine moved off of well	12-19 1978
Well seal-Material used Bento MITC	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used and information reported above are true to my	
Diameter of well bore to bottom of seal	best knowledge and belief.	
Number of sacks of cement used in well seal	[Signed] AMU O IL MULC Date D. 19.79 (Drilling Machine Operator)	
How was cement grout placed? DRI//ec/ 1N	Drilling Machine Operator's License No	301
	Water Well Contractor's Certification:	e i e e e e e e e e e e e e e e e e e e
A	This well was drilled under my jurisdiction and this report is	
Was a drive shoe used? Ves 🗆 No Plugs	true to the best of my knowledge and belief.	
Did any strata contain unusable water? 🗌 Yes 🖾 No	Name / 0 / 0 / A D P / A C O	
Type of water? depth of strata	Address ONA FIO OI	REGON
Method of sealing strata off	reimai ana 11 x 1 a DD	ula.A
Was well gravel packed? Ves Yo Size of gravel:	[Signed]	ictor)
Gravel placed from	Contractor's License No Date	1-81, \$9
(USE ADDITIONAL SH	EETS IF NECESSARY)	SP*45656-119