ATER WELL REPORT

le Original and	 	r L	VV P.	XIEW A	¥
rst Copy with the PATE ENGINEER,	 	software	 	STATE	(
TEM OPECON	-	-	 - " '=		

OF OREGON Apy 6956 State Permit No. .....

(1) OWNER:  Earl M. Burton	(11) WELL TESTS: Drawdown is amount water level is lowered below static level Parties.	
	Was a pump test made? Tyes No If yes, by whom? - Lifter Yield: 510 gal./min. with 40 ft. drawdown after 12 h	rs.
Address P. O. Box 46 Ontario, Oregon		
	2) 1) 1)	<del></del> -
(2) LOCATION OF WELL:	Bailer test gal./min. with ft. drawdown after h	ırs.
County Malheur owner's number, if any 1	Artesian flow NO g.p.m. Date	
SESW 14 14 Section 9 T. 18 SR. 47 EW.M.	Temperature of water 56 Was a chemical analysis made?   Yes	No
Bearing and distance from section or subdivision corner  S 63° 34' W a distance of 398.7 feet	(12) WELL LOG: Diameter of well8	
S 63° 34' W a distance of 398.7 feet from the NE corner of the SESW	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	ft.
TION CHE NE COLHEL O) THE SEAW		
	Formation: Describe by color, character, size of material and structure, a show thickness of aquifers and the kind and nature of the material in eastratum penetrated, with at least one entry for each change of formatic	ich on.
	MATERIAL FROM TO	
		<del>-</del> ···
(3) TYPE OF WORK (check):	Sandy loam for 30 feet,	
New Well ② Deepening □ Reconditioning □ Abandon □ Labandonment, describe material and procedure in Item 11.	17 feet slightly graveled	
abandonnent, describe material and procedure in rem 11.		
(4) PROPOSED USE (check): (5) TYPE OF WELL:		
Domestic M Industrial Municipal Rotary Driven M		_
Irrigation T Test Well Other Dug Bored		
(6) CASING INSTALLED: Threaded □ Welded □ Welde		
8 "Diam. from . O	14	
"Diam. from ft. to ft. Gage ft. Cage		<del></del> :
" Diam. from ft. to ft. Gage		
(7) PERFORATIONS: Perforated?		
Type of perforator used Slotted		
SIZE of perforations 1/4 in. by 6 in.		
564 perforations from 0 ft. to 47 ft.		
perforations from ft. to ft.		
perforations from		
perforations from		
perforations fromft. toft.		
(8) SCREENS: Well screen installed   ▼ Yes □ No		
Manufacturer's Name Parma Water Lifter		
Type bronze rod Model No.		—
$\frac{21}{2}$ . Slot size $\frac{1}{8}$ Set from $\frac{45}{5}$ ft. to $\frac{47}{5}$ ft.		
Dram, Slot size Set from ft. to ft.	Work started May 1 157. Completed May 15 19	/ ك
(9) CONSTRUCTION:	(13) PUMP:	
Was well gravel packed? ☐ Yes 🏗 No Size of gravel:	Manufacturer's Name Berkeley	
Gravel placed from ft. to ft.	Type: Centrifugal H.P. 5	
Was a surface seal provided?   Yes  No To what depth? ft.		
Material used in seal—	Well Driller's Statement:	
Did any strata contain unusable water?   Yes   No	This well was drilled under my jurisdiction and this report true to the best of my knowledge and belief.	is
Type of water? Depth of strata	A / C - D : / T	
Method of sealing strata off	NAME (Parson firm or composition) (Type or print)	
(10) WATER LEVELS:	Address 27/ S. E. 6th ave ONTARION	OR.
Static level 10 ft. below land surface Date May 1,	Address 2 7 3 E TONG CONTARION	× °
Artesian pressure lbs. per square inch Date	Driller's well number 226	••••
Log Accepted by:	150 miles Al Stroot	
	[Signed] (Well Driller)	
[Signed] Date, 19	License No. 226 Date Livre 30, 19.	<u>5 F</u>
\		_