NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(Please type or prost)	- INGINEER	_
(Do not write above this EALEM	OREGON Permit	No

(1) OWNER:	(10) LOCATION OF WELL:		
Name Charley McCoy	County Malheur Driller's well no	umber	
Address Gen. Del. Ironside, Oregon	S. W4 S. E 4 Section 9 T. 13S	_{R.} 39 E	W.M.
	Bearing and distance from section or subdivisi		
(2) TYPE OF WORK (check):	Dearing and distance from section of Subdivisi	on corner	
New Well □ Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.			
	(11) WATER LEVEL: Completed w	rell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found betwe	en 731 &	751 ft.
Rotary Driven Domestic Industrial Municipal	Static level 2 ft. below land s	surface. Date 5-	<u>-5-73</u>
Cable Jetted Irrigation Test Well Other	Artesian pressure lbs. per squar	re inch. Date	
CASING INSTALLED: Threaded Welded To the Diam from 1 to 37 tt. Gage 250	(12) WELL LOG: Diameter of well 1	below casingl.?	2
	Depth drilled 293 ft. Depth of compl	leted well 293	3 st.
	Formation: Describe color, texture, grain size	and structure of r	naterials
	and show thickness and nature of each stratus	m and aquifer pe	netrated,
	with at least one entry for each change of forma position of Static Water Level and indicate prin		
PERFORATIONS: Perforated? Yes No.	W.	 	
Type of perforator used	MATERIAL	From To	SWL
Size of perforations in. by in.	Clay & Gravel	 8 19 	
perforations from ft. to ft.	Med. to Coarse Gravel	1/ 1 77 1	
perforations from	Yellaw Clay & Boulders	11 48	
perforations from ft. to ft.	Blue Cley	48 73	
	Sendy Blue Clay W/B	78 75	91
(7) SCREENS: Well screen installed? Yes No	Blue Clay	75 95	49.
Manufacturer's Name	Med. to Small Gravel W/B	95 98	6} 1
Type Model No	Blue Clay	98 145	
Diam Slot size Set from ft. to ft.	Sandy Blue Clay W/B	145 149	
Diam Slot size Set from ft. to ft.	l	149 160	
	Blue Clay	160 164	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Sandy Blue Clay W/B	164 175	
	Herd Blue Clay	175 177	
Was a pump test made? The Ves No If yes, by whom? Page Bros		177 182	51
gal./min. with 210 ft. drawdown after 4 hrs.	Sandy Blue Clay W/B	182 220	
" "	Sticky Blue Clay	220 238	
" " "	Hard Brown Clay W/B	238 268	
Bailer test gal./min. with ft. drawdown after hrs.	Blue Clay	268 273	
	Soapstone (caving)	273 293	-21
'esian flow g.p.m.	Prown Clay		
perature of water 8 Depth artesian flow encountered ft.	Work started 4-30 1973 Complete	ed 5-5	1973
(9) CONSTRUCTION:	Date well drilling machine moved off of well	5 - 5	1973
` '	Drilling Machine Operator's Certification:	•	
Well seal—Material usedComont	This well was constructed under my		vision.
Well sealed from land surface toft.	Materials used and information reported		
Diameter of well bore to bottom of sealli in.	best knowledge and belief.	- //10	_
Diameter of well bore below seal12 in.	[Signed] (Drilling Machine Operator)	Date 6	بسكر19 ,.
Number of sacks of cement used in well seal3sacks	Drilling Machine Operator's License No.	65	
Number of sacks of bentonite used in well seal sacks	Drining Machine Operator's Encense No.		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons		lakiam a. 3 41-1	
of water lbs./100 gals.	This well was drilled under my jurisd true to the best of my knowledge and bel		eport 18
Was a drive shoe used? Yes □ No Plugs Size: location ft.	Name PAGE BROTHERS DRILLI	NG	
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Type or pri	nt)
Type of water? depth of strata	AddressRT., 2 Box 371 WAL	E OREGON	
	00/1/10/10	V	
Method of sealing strata off	[Signed]	9	
Was well gravel packed? Yes No Size of gravel:	[Signed]	-6-73	
Gravel placed from ft. to ft.	Contractor's License No Date		
	PERMO TE MECHOCADAN		2447070 110