## WATER WELL REPORT STATE OF OREGON



## A CENT LU

JUN 2 1 1984 state Well No. ..... 1954

PLEASE TYPE or PRINT IN SWEEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:	
Name ALVIN ANDERSON	County MAL HUER Driller's well number 4	
Address P.O. Box 3282	NE 4 5W 4 Section 15T. 195 R.	46e W.M.
City NYSS A State OREGON	Tax Lot # Lot Blk	Subdivision
(2) TYPE OF WORK (check):	Address at well location:	-
New Well ☑ Deepening □ Reconditioning □ Abandon □		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well	~ ~ ~
	Depth at which water was first found	295 ft.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level 260 ft. below land surface. Date 5 - 10 - 8	
Rotary Air	In tental processes	
Rotary Mud	(12) WELL LOG: Diameter of well below cas	ing
(5) CASING INSTALLED: Steel  Plastic	Depth drilled \( \frac{1}{20} \) ft. Depth of com	
(5) CASING INSTALLED: Steel  Plastic  Threaded  Welded	Formation: Describe color, texture, grain size and structure of materials; and show	
12 "Diam from +/ ft to 1/00 ft. Gauge	thickness and nature of each stratum and aquifer penetral for each change of formation. Report each change in posi	
12 "Diam from 160 ft. to 360 ft. Gauge	and indicate principal water-bearing strata.	
LINER INSTALLED:	MATERIAL I	From To SWL
"Diam. from	Soil	0 4
(a) DEDEOD AUTONS	Brown clay (gravel)	4 25
(6) PERFORATIONS: Perforated? □ Yes ⋈ No Type of perforator used	Brown clay (sandy)	25 120
Size of perforations in. by in.	Brown Clay (hard) /	20 130
	Brown Clay (sandy) /	30 240
perforations from	Brown Sandstone (Fine) 2	40 245
perforations from	Brown clay (sandy) 3	45 293
perforations from	Conclomerate Brown (Pine) &	193 295 260
(7) SCREENS: Well screen installed?   Yes  No	Brown sand fine gravel	
Manufacturer's Name	brown clay 3	195 340
Type Model No	Brown elay (soft) 3	340 345
Diam. Slot Size Set from ft. to ft.		355
Diam.         Slot Size         Set from         ft. to         ft.		55 380 3/0_
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		80 400
200011 20001		00 400 00
Was a pump test made? X Yes \( \subseteq No \) If yes, by whom? Owner	Blue Clay Greek Sand-	(72)
egal/min. with 100 ft. drawdown after 8 hrs.		20 4/25
		125 450
Air test gal./min. with drill stem at ft. hrs.	Blue Clay	50 480
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.	11.20	
perature of water 18 Depth artesian flow encountered ft.	Work started 4-28 1984 Completed	<u>5-18 1984</u>
(9) CONSTRUCTION: Special standards: Yes \( \text{No } \text{N} \)	Date well drilling machine moved off of well	5-20 1984
Well seal-Material used Nortland Cement	(unbonded) Water Well Constructor Certification (if applicable):	
Well sealed from land surface to		
Diameter of well bore to bottom of seal	and information reported above are true to my best knowledge and belief.  [Signed]	
Diameter of well bore below seal		
Number of sacks of cement used in well seal	Bonded Water Well Constructor Certification	
How was cement grout placed? growtp.u.y.p	Bond 7-1933149 Issued by: Miller Group of Jexas Surety Company Name 1	
	This well was drilled under my jurisdiction a	and this report is true to
Was pump installed? VCS Type INY. HP 10.0 Depth 410 ft.	the best of my knowledge and belief.	
Was a drive shoe used? ☐ Yes M No Plugs	(Person, firm or corporation) (Type or print)	
Did any strata contain unusable water?   Yes  No	Address P.O. BOX 41 Jamisson OR 97909	
Type of Water? depth of strata	01111010	
Method of sealing strata off	[Signed] All Market Well Constructor	
Was well gravel packed? ☐ Yes No Size of gravel:	Date	18 , 1984
Gravel placed fromft. toft.		